

# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20140627-E81680  
**Report Reference** E81680-20140625  
**Issue Date** 2014-JUNE-27

**Issued to:** R STAHL SCHALTGERAETE GMBH  
AM BAHNHOF 30  
74638 WALDENBURG GERMANY

**This is to certify that  
representative samples of**

PROCESS CONTROL EQUIPMENT FOR USE IN  
HAZARDOUS LOCATIONS; PROCESS CONTROL  
EQUIPMENT FOR USE IN ZONE CLASSIFIED  
HAZARDOUS LOCATIONS.


See Addendum Page

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.


**Standard(s) for Safety:** See Addendum Page

**Additional Information:** See the UL Online Certifications Directory at  
[www.ul.com/database](http://www.ul.com/database) for additional information

Only those products bearing the UL Listing Mark for the US and Canada should be considered as being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US and Canada.

The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and "US" identifiers:  the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.



William R. Carney, Director, North American Certification Programs  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at [www.ul.com/contactus](http://www.ul.com/contactus)



# CERTIFICATE OF COMPLIANCE

**Certificate Number** 20140627-E81680  
**Report Reference** E81680-20140625  
**Issue Date** 2014-JUNE-27

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Panel-mounted illuminated pushbutton Type 8018/32; followed by 1, 2, or 3; followed by 3; followed by additional suffixes.

Intrinsically Safe for use in Class I, Division 1, Groups A, B, C and D; Class 1, Zone 0, AEx ia IIB T4; Class I, Zone 1, AEx ia IIC T4; Class I, Zone 0, Ex ia IIB T4; and Class I, Zone 1, Ex ia IIC T4 Hazardous Locations when installed in accordance with Control Drawing No. 80 186 01 31 3.

#### Standard(s) for Safety:

UL 913, Intrinsically Safe Apparatus and Associated Apparatus for Use in Class I, II, and III, Division 1, Hazardous (Classified) Locations.


UL 60079-0, Explosive atmospheres – Part 0: Equipment – General requirements.

UL 60079-11, Explosive Atmospheres – Part 11: Equipment Protection by Intrinsic Safety “i”.

CAN/CSA C22.2 No. 157-92, Intrinsically Safe and Non-incendive Equipment for Use in Hazardous Locations.

CAN/CSA-C22.2 No. 60079-0:11, Explosive atmospheres — Part 0: Equipment — General requirements.

CAN/CSA-C22.2 No. 60079-11:11, Explosive atmospheres — Part 11: Equipment protection by intrinsic safety “i”.



William R. Carney, Director, North American Certification Programs  
UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at [www.ul.com/contactus](http://www.ul.com/contactus)