

## **QPS Evaluation Services Inc**

Testing, Certification and Field Evaluation Body Accredited in Canada, the USA, and Internationally

Page 1 of 2

File LR1504

Ex Markings for M Series;

non-hazardous locations

Zone 21, [AEx ia Da] IIIC

[Ex ia Ga] IIA/IIB/IIC

[Ex ia Da] IIIC

Associated Apparatus for installation in

Class I, Zone 1, [AEx ia Ga] IIA/IIB/IIC

[Ex ia Ga] CI I, Div 1, Groups ABCD

[Ex ia Da] CI II, Div 1, Groups EFG

# **CERTIFICATE OF COMPLIANCE**

(ISO TYPE 3 CERTIFICATION SYSTEM)

Issued to Solexy Srl

Address Via Enrico Fermi 2

I-25015 Desenzano del Garda (BS)

Italy

Project Number LR1504-3R2

Product Antenna Couplers

Model Number RX, SX, UX and M series

Ratings 250Vdc/ 250Vac 50-60Hz

(Provides a Type 4X connection when connected to a Type 4X rated enclosure)

Special Conditions of Use See Appendix A

Markings <u>Ex Markings for RX, SX and UX Series;</u>

Class I, Zone 1, AEx db mb [ia Ga] IIA/IIB/IIC

T6...T5 Gb

Zone 21, AEx mb tb [ia Da] IIIC T80°C...T100°C

Db

Ex db mb [ia Ga] IIA/IIB/IIC T6...T5 Gb Ex mb tb [ia Da] IIIC T80°C...T100°C Db

CI I, Div 1, Groups ABCD CI II, Div 1, Groups EFG

[Ex ia Ga] IIC [Ex ia Da] III

Applicable Standards CAN/CSA C22.2 No. 60079-0:2015\* UL 60079-0, edition 6.0\*

CAN/CSA C22.2 No. 60079-1:2016 UL 60079-1, edition 7.0 UL 60079-11, edition 6.0\* CAN/CSA C22.2 No. 60079-11:2014\* CAN/CSA C22.2 No. 60079-18:2016 UL 60079-18, edition 4.0 CAN/CSA C22.2 No. 60079-31:2015 UL 60079-31, edition 2.0 CAN/CSA C22.2 No. 60950-1:2007\* UL 60950-1, edition 2.0\* UL 1203, edition 5.0 CAN/CSA C22.2 No. 25-17 CAN/CSA C22.2 No. 30-M1986 UL 913, edition 8.0 CAN/CSA C22.2 No. 157-92 UL 508, edition 17\*

Note\* - only the following standards apply to the M series

Factory/Manufacturing Location Same as Applicant

**Statement of Compliance**: The product(s) identified in this Certificate and described in the Report covered under the above referenced project number have been investigated and found to be in compliance with the relevant requirements of the above referenced standard(s). As such, they are eligible to bear the QPS Certification Mark shown below, in accordance with the provisions of QPS's Service Agreement.



Issued By: Dave Adams, P. Eng.

Manager, Hazardous Locations Department

Signature: Date: December 7, 2021

81 Kelfield St., Units 7-9, Toronto, ON M9W 5A3 Tel: 416-241-8857; Fax: 416-241-0682



## **QPS Evaluation Services Inc**

Testing, Certification and Field Evaluation Body Accredited in Canada, the USA, and Internationally

Page 2 of 2

File LR1504

# **CERTIFICATE OF COMPLIANCE**

(ISO TYPE 3 CERTIFICATION SYSTEM)

### Appendix A - Special Conditions of Use:

- The RX, SX, UX and M series antenna coupler must be connected to an RF source with a minimum internal impedance of 50Ω.
- 2. The RX, SX, UX, and M series antenna coupler does not provide any RF Power Limitation. The threshold hold power must be limited by the end-user.
- The RX/SX antenna couplers marked with an ambient temperature range of -40°C to +70°C /85°C shall be limited to a
  maximum RF input of 2 watts.
- Since Annex F from IEC/CSA/UL 60079-11 was applied; the UX and M series antenna couplers shall only be supplied by equipment rated with a maximum overvoltage category II.
- The M series antenna is only intended to be installed in a non-classified location and shall be connected to a high-integrity earth point (IS ground) not exceeding 1Ω or connected to an equipotential bonding system in accordance with the CEC/NEC.

**Statement of Compliance**: The product(s) identified in this Certificate and described in the Report covered under the above referenced project number have been investigated and found to be in compliance with the relevant requirements of the above referenced standard(s). As such, they are eligible to bear the QPS Certification Mark shown below, in accordance with the provisions of QPS's Service Agreement.



Issued By: Dave Adams, P. Eng.

Manager, Hazardous Locations Department

Signature: Date: December 07, 2021

QSD 34HL Rev 00