CERTIFICATE OF COMPLIANCE

Certificate Number Report Reference Issue Date

20130715-E81680 E81680-20070614 2013-JULY-15

Issued to: R STAHL SCHALTGERAETE GMBH AM BAHNHOF 30 74638 WALDENBURG GERMANY

This is to certify that representative samples of

PROCESS CONTROL EQUIPMENT FOR USE IN HAZARDOUS LOCATIONS; PROCESS CONTROL EQUIPMENT FOR USE IN ZONE CLASSIFIED HAZARDOUS LOCATIONS

See Addendum Page

Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

Standard(s) for Safety: Additional Information: See Addendum Page See the UL Online Certifications Directory at www.ul.com/database for additional information

Only those products bearing the UL Listing Mark for the US and Canada should be considered as being covered by UL's Listing and Follow-Up Service meeting the appropriate requirements for US and Canada.

The UL Listing Mark for the US and Canada generally includes: the UL in a circle symbol with "C" and "US" identifiers: ^(U) the word "LISTED"; a control number (may be alphanumeric) assigned by UL; and the product category name (product identifier) as indicated in the appropriate UL Directory.

Look for the UL Listing Mark on the product.

William R. Caro

William R. Carney, Director, North American Certification Programs

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at www.ul.com/contactus

CERTIFICATE OF COMPLIANCE

Certificate Number Report Reference Issue Date 20130715-E81680 E81680-20070614 2013-JULY-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Standards for Safety:

UL 913, Intrinsically Safe Apparatus and Associated Apparatus for Use in Class I, II, and III, Division 1, Hazardous (Classified) Locations.

UL 60079-0 & CAN/CSA-C22.2 No. 60079-0:11, Explosive atmospheres – Part 0: Equipment – General requirements.

UL 60079-11 & CAN/CSA-C22.2 No. 60079-11:11, Explosive Atmospheres – Part 11: Equipment Protection by Intrinsic Safety "i".

CAN/CSA C22.2 No. 157-92, Intrinsically Safe and Non-incendive Equipment for Use in Hazardous Locations.

Products Covered:

USL: Class I, Division 1, Groups A, B, C and D; Class I, Zone 0, AEx ia IIB T4; and Class I, Zone 1, AEx ia IIC T4 Hazardous Locations.

CNL:Class I, Division 1, Groups A, B, C and D; Class I, Zone 0, Ex ia IIB T4; and Class I, Zone 1, Ex ia IIC T4 Hazardous Locations.

Pilot Light Type 8013/32 is intrinsically safe when installed per Control Drawing No. 80-136-01-31-3.

William R. Caro

William R. Carney, Director, North American Certification Programs

U

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <u>www.ul.com/contactus</u>