

Electrical Equipment for Explosive Atmospheres Certificate of Type Verification

Applicant	Wan Jiun Technology Co., Ltd.								
Applicant address	11F., No.896, Jingguo Rd. Luzhu Dist., Taoyuan City Taiwan	TEL	+886-3-3161585						
Manufacturer	R. STAHL Schaltgeräte GmbH								
Manufacturer address	Am Bahnhof 30 74638 Waldenburg Germany	TEL	+49(0)7942/ 943-4162						
Name of product Type	Plug 8571 Series								
Ex marking	Ex eb IIC T6... T5 Gb Ex tb IIC T81°C Db								
Certificate No.	(ITRI)2023 第 07-00082X 號								
Date of first Issue	June 05, 2023								
Date of renewal	June 03, 2026								
Valid period	June 05, 2026 to June 04, 2029								
Standards:	IEC 60079-0 : 2017 ; IEC 60079-7 : 2017 ; IEC 60079-31 : 2013.								
Ratings:	Maximum voltage rating : 690 V AC Maximum current rating : 32 A.								
Ambient temperature:	For plug type 8571/*2-***-* with sealing ring made of D0122-01 : -40°C ~ +40°C... +65°C / T6 ... T5 by current range 16 A ... 32 A For plug type 8571/*2-***-* with sealing ring made of D0123-01 : -50°C ~ +40°C... +65°C / T6 ... T5 by current range 16 A ... 32 A								
Main components:	Enclosure (plastic), gasket, clamp insert, contact pin.								
Type variants:	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">Type</th> <th>8571/a2-bcc-de</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">a</td> <td>Design 1 = Standard 2 = North America</td> </tr> <tr> <td style="text-align: center;">bcc</td> <td> Poles / Position for earth contact and voltage / frequency / colour 4** = 3P+PE 402 = >50 V, >300-500 Hz, 25 A(green) 403 = 380 V, 50 Hz(red) 404 = 100-130 V, 50/60 Hz(yellow) 405 = 600-690 V, 50/60 Hz(black) 406 = 380-415 V, 50/60 Hz(red) 407 = 480 V, 50/60 Hz(red) 409 = 200-250 V, 50/60 Hz(blue) 410 = >50 V, 100-300 Hz, 25 A(green) 411 = 440-460 V, 60 Hz(red) 5** = 3P+N+PE 502 = >50 V, >300-500 Hz, 25 A(green) 503 = 220/380 V, 50 Hz(red) </td> </tr> </tbody> </table>			Type	8571/a2-bcc-de	a	Design 1 = Standard 2 = North America	bcc	Poles / Position for earth contact and voltage / frequency / colour 4** = 3P+PE 402 = >50 V, >300-500 Hz, 25 A(green) 403 = 380 V, 50 Hz(red) 404 = 100-130 V, 50/60 Hz(yellow) 405 = 600-690 V, 50/60 Hz(black) 406 = 380-415 V, 50/60 Hz(red) 407 = 480 V, 50/60 Hz(red) 409 = 200-250 V, 50/60 Hz(blue) 410 = >50 V, 100-300 Hz, 25 A(green) 411 = 440-460 V, 60 Hz(red) 5** = 3P+N+PE 502 = >50 V, >300-500 Hz, 25 A(green) 503 = 220/380 V, 50 Hz(red)
Type	8571/a2-bcc-de								
a	Design 1 = Standard 2 = North America								
bcc	Poles / Position for earth contact and voltage / frequency / colour 4** = 3P+PE 402 = >50 V, >300-500 Hz, 25 A(green) 403 = 380 V, 50 Hz(red) 404 = 100-130 V, 50/60 Hz(yellow) 405 = 600-690 V, 50/60 Hz(black) 406 = 380-415 V, 50/60 Hz(red) 407 = 480 V, 50/60 Hz(red) 409 = 200-250 V, 50/60 Hz(blue) 410 = >50 V, 100-300 Hz, 25 A(green) 411 = 440-460 V, 60 Hz(red) 5** = 3P+N+PE 502 = >50 V, >300-500 Hz, 25 A(green) 503 = 220/380 V, 50 Hz(red)								

Certificate issued by

Industrial Technology Research Institute
195 Sec. 4, Chung Hsing Rd., Chutung, Hsinchu, 310401, Taiwan



Electrical Equipment for Explosive Atmospheres

Certificate of Type Verification

Certificate No.: (ITRI)2023 第 07-00082X 號

Applicant	Wan Jiun Technology Co., Ltd.	
	Type	8571/a2-bcc-de
	bcc	Poles / Position for earth contact and voltage / frequency / colour 5** = 3P+N+PE 504 = 57/100-75/130 V, 50/60 Hz(yellow) 505 = 347/600-400/690 V, 50/60 Hz(black) 506 = 200/346-240/415 V, 50/60 Hz(red) 507 = 277/480 V, 50/60 Hz(red) 509 = 120/208-144/250 V, 50/60 Hz(blue) 510 = >50 V, 100-300 Hz, 25 A(green) 511 = 250/440-265/460 V, 60 Hz(red)
	d	Sealing material B = Silicone free S = Containing silicone
	e	Additional parameter that do not affect the explosion protection of the equipment.
Specific conditions of use:	The plug must not be used in dust areas where highly charge-generating processes, machine friction and separation processes, electron spraying (e.g. around electrostatic coating systems) and pneumatically conveyed dust occur. WARNING - THE PLUG SHALL BE FREE FROM WATER AND DUST BEFORE IS INSERTED TO THE SOCKET. WARNING – DO NOT OPEN WHEN ENERGIZED. WARNING – POTENTIAL ELECTROSTATIC CHARGING HAZARD – SEE INSTRUCTIONS. WARNING – THE PLUG SHALL BE FIRMLY MOUNTED AT THE SOCKET IN ORDER TO ENSURE THE INGRESS PROTECTION (IP). WARNING – TEMPERATURE AT THE ENTRY POINTS HIGHER THAN +70°C. A PROPER SELECTION OF CABLE AND CABLE GLANDS OR CONDUCTORS IN CONDUIT IS REQUIRED.	
Approval reference:	The assessment of the above equipment is based on the review of IECEx Certificate of Conformity (IECEX PTB 20.0003X Issue No.: 1) issued by Physikalisch-Technische Bundesanstalt (PTB), Germany and the associate test reports (DE/PTB/ExTR20.0002/01).	
Certificate history:	Issue 1 (B202300104)	(2023-06-05)
	Issue 2 (B202600194)	(2026-06-03)

Certificate issued by

Industrial Technology Research Institute
 195 Sec. 4, Chung Hsing Rd., Chutung, Hsinchu, 310401, Taiwan

