





Conduit Fittings

Series EM, NP

Selection Table

Version	Nominal diameter D	Length L [mm]	Type	Art. no.	Weight kg
Conduit fitting Series EM with 2 x female unions  <small>00886E00</small>  <small>03553E00</small>	NPT 1/2"	39	EM1	108102	0.090
	NPT 3/4"	39	EM2	108103	0.080
	NPT 1"	51	EM3	108104	0.150
	NPT 1 1/2"	51	EM5	108105	0.270
	NPT 2"	51	EM6	108106	0.450
	NPT 2 1/2"	65	EM7	108107	0.650
	NPT 3"	65	EM8	108108	0.800
	Male nipple Series NP with 2 x male unions  <small>00678E00</small>  <small>03554E00</small>	NPT 1/2"	48	NP1	108398
NPT 3/4"		48	NP2	108399	0.060
NPT 1"		60	NP3	108400	0.100
NPT 1 1/2"		55	NP5	108402	0.150
NPT 2"		55	NP6	108403	0.200
NPT 2 1/2"		68	NP7	108404	0.450
NPT 3"		68	NP8	108405	0.700

Explosion Protection

Global (IECEX)

Gas and dust	IECEX CES 10.0001 X Ex d IIC / Ex e II Ex tD A21 IP66/67
--------------	--

Europe (ATEX)

Gas and dust	CESI 01 ATEX 104 U Ⓢ II 2 G Ex d IIC / Ex e II Ⓢ II 2 D Ex tD A21 IP66/67
--------------	---

Certifications and certificates

Certificates	IECEX, ATEX, Kazakhstan (TR), Russia (TR), Belarus (TR)
--------------	---

Technical Data

Mechanical data

Material	galvanized steel
----------	------------------

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.