

IS930.M1 Tablet Set mining ROW 订货号 307073



- Explosion-protected tablet Ideal for Mobile Worker concepts
- Android Enterprise Recommended
- zero touch capability
- certified for mining industry
- user-friendly operation and easy to handle with hand strap
- individually programmable buttons
- display can be operated with gloved fingers

<STEPREF A="AT_TitleWeb-shop" O="PV 2276227"



The robust and powerful tablet is the ideal partner for our MOBILE WORKER concepts in mining ambient conditions. The IoT generation tablet is Android Enterprise Recommended. Its zero touch capability makes it quick to use and ideal for maintenance applications in an IoT environment. The 8-inch display, two freely programmable buttons, a long-life battery, a practical hand strap and a separate leather bag with a shoulder/belt or carry strap system are further highlights.

技术数据

防爆

使用范围 (防火湿保护)	M1 M2
应用范围	矿用 M1、M2
适用范围	采矿业: 欧盟 (CE / ATEX) 全球 (IECEX) 南非 (SANS) 澳大利亚和新西兰 (ANZEx)
IECEX 认证	EPS 19.0063X
ATEX 认证	EPS 19 ATEX 1 128 X
SANS 认证	MTEEx 0901/20.0014
ANZEx 认证	ANZEx 20.2001X
IECEX 防火湿保护	Ex ia I Ma IP64
ATEX 防火湿保护	I M1 Ex ia I Ma IP64
SANS 防火湿保护	Ex ia I Ma IP64
ANZEx 防火湿保护	Ex ia I Ma

电气数据

处理器型号	Qualcomm SDM660 Octa-core
内存	4 GB
数据存储器	64 GB 内存 + 高达 128 GB 的 SD 卡
操作系统	Android 10 (upgr. 13)
移动标准	2G , 3G , 4G
介质接口	WLAN 802.11 a/b/g/n/ac/e/k/r/h
可选数据接口 1	蓝牙 5
可选数据接口 2	13MP-AF-摄像头 (后置)
附件 3/选项框	5MP 前置摄像头
SD 卡型号/容量	microSD/最大 128 GB

IS930.M1 Tablet Set mining ROW 订货号 307073

电气数据

SIM 卡数量	单 SIM 卡
SIM 卡尺寸	micro

显示屏

显示屏尺寸, 英寸	8.00
显示屏尺寸 cm	20.32
显示屏分辨率	全高清 1200 x 1920 像素
触摸屏	电容式
触摸屏材料	大猩猩玻璃, 康宁第三代
背光照明灯	LED 技术

环境条件

环境温度	-20 – 60
环境温度	-20 °C ... +60 °C

机械数据

防护等级 (IP)	IP68
MIL 标准	810G (h/l 温度, 冲击, 振动)
宽度	156 mm
高度	237 mm
深度	22 mm
重量	890 g
重量	1.96 lb

保留更改技术数据、尺寸、重量、结构和交付方式的权利。图片不具有法律约束力。