

IS120.1 Mobiltelephone Set 订货号 317308



- Telephony and messaging (SMS)
- amplified loudspeaker for noisy work environments
- powerful battery for long work shifts
- 4G telephony

<STEPREF A="AT_TitleWeb-shop" O="PV 2699989"



The explosion-protected, powerful and highly robust mobile phone with telephony and messaging (SMS) as its main functions. With its good heft, the device is designed for easy handling that does not detract from the task at hand. The powerful battery makes it ideal for long work shifts. It is ideally suited for efficient work communication.

技术数据

防爆

使用范围 (区)	1 2 21 22
应用范围	1 区 , 21 区 2 区 , 22 区
适用范围	欧盟 (CE / ATEX) 全球 (IECEX) 英国 (UKEX) 巴西 (INMETRO)
IECEX 认证	EPS 21.0040X
ATEX 认证	EPS 21 ATEX 1 107 X
UKCA 认证	CML 21UKEX21329X
INMETRO 认证	BRA 21.GE0033X
IECEX 气体防爆	Ex ib IIC T4 Gb
ATEX 气体防爆	Ex II 2G Ex ib IIC T4 Gb
ATEX 粉尘防爆	Ex II 2D Ex ib IIIC T135°C Db
UKCA 气体防爆	Ex ib IIC T4 Gb
UKCA 粉尘防爆	Ex ib IIIC T135°C Db
INMETRO 气体防爆	Ex ib IIC T4 Gb
INMETRO 粉尘防爆	Ex ib IIIC T135°C Db

电气数据

内存	2 GB
数据存储器	16 GB
操作系统	Android 10
移动标准	2G , 3G , 4G
可选数据接口 1	蓝牙 5
SD 卡型号/容量	microSD/最大 128 GB
SIM 卡数量	双 SIM 卡

IS120.1 Mobiltelephone Set 订货号 317308

电气数据

SIM 卡尺寸	micro
---------	-------

显示屏

显示屏尺寸, 英寸	2.40
显示屏尺寸 cm	6.10
触摸屏材料	大猩猩玻璃, 康宁第三代
背光照明灯	LED 技术

环境条件

环境温度	-20 – 60
------	----------

机械数据

防护等级 (IP)	IP68
MIL 标准	810H
宽度	60 mm
高度	140 mm
深度	26 mm
重量	214 g
重量	0.47 lb

保留更改技术数据、尺寸、重量、结构和交付方式的权利。图片不具有法律约束力。