

IS655.2 Smartphone Set ROWno camera 订货号 317575



- Slim and elegant industrial design
- without camera
- push to talk key for uncomplicated team communication
- Android Enterprise Recommended
- zero touch capable
- MDM compatible

<STEPREF A="AT_TitleWeb-shop" O="PV 2700263"



The slim, explosion-protected smartphone combines elegant design with extreme ruggedness. It features state-of-the-art technology, a fast processor and a PTT key for uncomplicated team communication. The lightweight smartphone is Android Enterprise Recommended, zero touch capable and MDM compatible.

技术数据

防爆

使用范围 (区)	2 22
使用范围 (Division)	Class I, Division 2 Class II, Division 2 Class III, Division 2
应用范围	2 区 , 22 区
适用范围	欧盟 (CE / ATEX) 全球 (IECEX) 美国 (NEC) 加拿大 (CEC) 韩国 (KCS)
IECEX 认证	EPS 19.0064X
ATEX 认证	EPS 19 ATEX 1 129 X
NEC 认证	80039336
CEC 认证	80039336
KCS 认证	19-KA4BO-0971X 19-KA4BO-0972X
IECEX 气体防爆	Ex ic IIC T4 Gc IP54
IECEX 粉尘防爆	Ex ic IIIC T135°C Dc IP64
ATEX 气体防爆	Ex II 3G Ex ic IIC T4 Gc IP54
ATEX 粉尘防爆	Ex II 3D Ex ic IIIC T135°C Dc IP64
NEC 气体防爆	Class I, Div 2, Groups A, B, C, D, T4
NEC 粉尘防爆	Class II, Div 2, Groups F, G , T135°C Class III, Div 2
CEC 气体防爆	Class I, Div 2, Groups A, B, C, D, T4
CEC 粉尘防爆	Class II, Div 2, Groups F, G , T135°C Class III, Div 2
ATEX 气体防爆	Ex ic IIC T4

IS655.2 Smartphone Set ROWno camera 订货号 317575

电气数据

处理器型号	Helio P22 (MT 6762V)
内存	3 GB
数据存储器	32 GB
操作系统	Android 10
移动标准	2G , 3G , 4G
可选数据接口 1	蓝牙 5
SD 卡型号/容量	microSD/最大 128 GB
SIM 卡数量	双 SIM 卡
SIM 卡尺寸	micro

显示屏

显示屏尺寸, 英寸	5.50
显示屏尺寸 cm	13.97
显示屏分辨率	720 x 1440 像素
触摸屏材料	大猩猩玻璃, 康宁第三代
背光照明灯	LED 技术

环境条件

环境温度	-10 – 60
------	----------

机械数据

防护等级 (IP)	IP68
MIL 标准	810G (h/l 温度, 冲击, 振动)
宽度	76 mm
高度	153 mm
深度	13 mm
重量	203 g
重量	0.45 lb

保留更改技术数据、尺寸、重量、结构和交付方式的权利。图片不具有法律约束力。