

## IS-TH1MR.M1 Trigger Handle Set mid-range 订货号 317635



- Reliable data capture and processing of 1D or 2D barcodes
- direct data transfer via ISM interface
- power supply via connected device, thus no battery required
- direct interface connection with device, no Bluetooth® required

<STEPREF A="AT\_TitleWeb-shop" O="PV 2700897"



The mobile multifunctional set consisting of a Trigger Handle (hand-held barcode scanner) and the IS530.x industrial smartphone is a flexible duo for reliable data capture in industrial areas. The HID-active, ready-to-use high-performance scanner captures any 1D or 2D barcodes at close range of up to 6 metres or distances up to 18 metres via the reliable Zebra OEM imager scan engines. The data is further processed directly via the IS530.x smartphone connected via the ISM interface.

### 技术数据

#### 防爆

|                |                                      |
|----------------|--------------------------------------|
| 防爆版本           | 无                                    |
| 使用范围 ( 防火湿保护 ) | M1<br>M2                             |
| 适用范围           | 欧盟 (CE / ATEX) 采矿业<br>全球 (IECEX) 采矿业 |
| IECEX 认证       | EPS 21.0029X                         |
| ATEX 认证        | EPS 21 ATEX 1 083 X                  |
| IECEX 气体防爆     | Ex ib op is IIC T4 Gb                |
| IECEX 粉尘防爆     | Ex ib op is IIIC T135°C Db           |
| IECEX 防火湿保护    | Ex ia op is I Ma                     |
| ATEX 气体防爆      | Ⓢ II 2G Ex ib op is IIC T4 Gb        |
| ATEX 粉尘防爆      | Ⓢ II 2D Ex ib op is IIIC T135°C Db   |
| ATEX 防火湿保护     | Ⓢ I M1 Ex ia op is I Ma              |

#### 环境条件

|      |          |
|------|----------|
| 环境温度 | -20 – 60 |
|------|----------|

#### 机械数据

|                |        |
|----------------|--------|
| 箱体防护等级 (IP) 正面 | IP68   |
| 箱体防护等级 (IP) 背面 | IP68   |
| 壳体材料           | 塑料     |
| 宽度             | 90 mm  |
| 高度             | 202 mm |
| 深度             | 125 mm |
| 重量             | 1 kg   |
| 重量             | 2.2 lb |

保留更改技术数据、尺寸、重量、结构和交付方式的权利。图片不具有法律约束力。