

Signalling devices



Audible signalling device Sounder

In flameproof enclosure

YA6S/21-DS0000-000003-ST0000-0000 Art. No. 284527



- Horn: Omnidirectional/max. 110 db(A)
- Type of protection: Ex d
- Class: IP66/67 (IEC 60529/NEMA 4X)
- Corrosion-resistant GRP enclosure
- Including fastening bracket
- 32 standardised preconfigured signal tones (compatible with PFEER/UKOOA)
- Separate signal tones can be selected (2 for AC, 3 for DC variants)
- Signal tone reduction can be set up to 18 dB(A)
- Connection for telephone systems/performance monitoring can be ordered as an option

MY R. STAHL YA6SA



The **YA6S product series** provides audible alarm signals which can be used to alert, warn or draw attention to equipment malfunction/start-up or any number of safety-related issues. Corrosion resistance is a key feature of the device; it is therefore ideal for applications in the harshest of environments, both onshore and offshore.

Technical Data

Explosion Protection

Scope of validity	European Union (ATEX) IECEX
Application range (zones)	1 2 21 22
IECEX gas certificate	IECEX EPS 20.0036X
IECEX gas explosion protection	Ex db IIC T6 / T4 Gb
IECEX dust certificate	IECEX EPS 20.0036X
IECEX dust explosion protection	Ex tb IIIC T80 °C / T100 °C Db
ATEX gas certificate	EPS 20 ATEX 1 076 X
ATEX gas explosion protection	⊕ II 2 G Ex db IIC T6 / T4 Gb
ATEX dust certificate	EPS 20 ATEX 1 076 X
ATEX dust explosion protection	⊕ II 2 D Ex tb IIIC T80 °C / T100 °C Db
Certificates	ATEX (BVIS), IECEX (BVIS)
Declaration of Conformity	ATEX (EUK)

Electrical Data

Rated operational voltage DC	12 ... 24 V
Rated operational current	0.3 A (T6)
Line monitoring	Yes
Tolerance	-10 ... 10 %

Acoustic Data

Sound pressure level	max. 110 dB(A) @ 1 m
Tone selection	Via DIL switch
Sound level	4
Volume control	Max. -18 dB(A) adjustment
Volume adjustment	Via DIL switch

Signalling devices

Audible signalling device Sounder

In flameproof enclosure

YA6S/21-DS0000-000003-ST0000-0000 Art. No. 284527



Ambient Conditions

Ambient temperature	-60 °C ... +50 °C (T6) -60 °C ... +70 °C (T4)
Functional ambient temperature	-40 °C ... +50 °C (T6) -40 °C ... +70 °C (T4)

Mechanical Data

Degree of protection (IP) (IEC 60529)	IP66
Enclosure material	Polyester (GRP), Glass fibre reinforced
Enclosure colour	Black
Silicone-free content	Contains silicone
Trumpet material	ABS, flame retardant
Max. solid connection terminals	2.5 mm ²
Max. finely stranded connection terminals	2.5 mm ²
Width	178.5 mm
Height	263.5 mm
Length	145 mm
Weight	3.64 kg
Weight	8.02 lb





Mounting / Installation

Connection type	Push in
Mounting part material	Stainless steel
Note about mounting	Provided


Components

Drilled holes	2 x M20
Cable glands and entries	Can be ordered as accessories
Stopping plugs	2 x dust cap

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



GRP Audible Signal Series YA6S without L-Bracket



GRP Audible Signal Series YA6S with L-Bracket

Accessories

Metal cable gland

Art. No.



Signalling devices



Audible signalling device Sounder




In flameproof enclosure

YA6S/21-DS0000-000003-ST0000-0000 Art. No. 284527

	Ex d and Ex e cable gland with compound for all types of armoured cables (SWA, wire-braid, tape) (nickel-plated brass) Type 20PX2K, M20 x 1.5	109428
	Ex d and Ex e cable glands with RapidEx sealing system for all types of unarmoured cables and wire-braid-armoured cables (nickel-plated brass) Type 20PX2K-REX, M20 x 1.5	246649
	Ex d and Ex e cable glands with compound for all types of unarmoured cables and wire-braid-armoured cables (nickel-plated brass) Type 20PXSS2K, M20 x 1.5	109441
	Ex d and Ex e cable glands with RapidEx sealing system for all types of unarmoured cables and wire-braid-armoured cables (nickel-plated brass) Type 20PXSS2K-REX, M20 x 1.5	246605

Mounting accessories


Art. No.

	Stainless steel L-bracket, standard version	221711
	Stainless steel L-bracket, long version	247371
	Adapter plate for pipe clamp fastening	256519
	Pipe clamp, R 1 1/4"	120812
	Pipe clamp, R 1 1/2"	120819
	Pipe clamp, R 2"	120823

Spare Parts

Shaped horn assembly kit

Art. No.

	Shaped horn YA60/YL60/YA6S/YL6S spare ATEX	213457
--	---	--------

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.