Installation Equipment and Accessories

Breather



8162/1-25-1 Art. No. 285801



- Improves safety by preventing condensation from building up in enclosures
- Continuous pressure equalisation between the enclosure and the environment
- Type of protection Ex e (increased safety), max. degree of protection IP65

MY R. STAHL 8162A



R. STAHL's 8162 series breathers provide continuous pressure equalisation between the inside of the enclosure and the atmosphere around the enclosure. This ventilation prevents moisture from entering the enclosure via the seals and condensing inside the enclosure. The breathers are made from moulded material and meet the requirements of degrees of protection up to IP65.

Technical Data

Explosion Protection	
Application range (zones)	1 2 21 22
IECEx gas certificate	IECEx PTB 06.0028
IECEx gas explosion protection	Ex eb IIC Gb
IECEx dust certificate	IECEx PTB 06.0028
IECEx dust explosion protection	Ex tb IIIC Db
ATEX gas certificate	PTB 01 ATEX 1018
ATEX gas explosion protection	
ATEX dust certificate	PTB 01 ATEX 1018
ATEX dust explosion protection	
Certificates	ATEX (PTB), IECEx (PTB), USA (FM)
Declaration of Conformity	ATEX (EUK)
Ambient Conditions	
Ambient temperature	-40 °C +70 °C
Mechanical Data	
Degree of protection (IP)	IP65
Degree of protection note	when installed in enclosure side: IP64 for lateral mounting IP65 for vertical mounting downwards
Material	Polyamide
Material 2	Glass fibre reinforced
Silicone-free	Yes
Width across corners	32.5 mm
Thread size	M25
Thread pitch	1,5 mm
Mounting instruction	only permitted in enclosures with through hole

Installation Equipment and Accessories

Breather




8162/1-25-1 Art. No. 285801

MAC	han	IC 2	l Data


medianical bata	
Nuts available	With nut
Packaging unit	20
Weight	400 g
Weight	0.88 lb

Technical Drawings - Subject to Alterations



Temperature-related pressure differences between the inside of the enclosure (P1) and the surrounding atmosphere (P2) are balanced by the breather. The amount of condensation forming in the enclosure is thus kept to a minimum.

Dimensional Drawings (All Dimensions in mm [inches]) - Subject to Alterations



Accessories

Locknut, plastic		Art. No.
	Material: Polyamide, version slotted on both sides Thread size: M25 x 1.5 1 piece	138596

Spare Parts

Flat gasket (standard), EPDM (-40 +75 °C)		Art. No.
	Material: EPDM M25 x 1.5 1 piece	111771

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.