

M25-M32 Art. No. 109389



- Ex e extensions made of glass fibre reinforced polyamide
- Wide selection of metric thread sizes

MY R. STAHL ACC1A



The plastic Ex e extensions make it possible to easily adapt thread sizes. There is a wide selection of different versions available for this. They have global certification according to IECEx and ATEX.

Technical Data

Explosion Protection

Application range (zones)	1, 2, 21, 22
IECEX gas certificate	IECEX PTB 16.0026X
IECEX gas explosion protection	Ex eb IIC Gb
IECEX dust certificate	IECEX PTB 16.0026X
IECEX dust explosion protection	Ex tb IIIC Db
ATEX gas explosion protection	Ⓔ II 2 G Ex eb IIC Gb
ATEX dust explosion protection	Ⓔ II 2 D Ex tb IIIC Db

Ambient Conditions


Ambient temperature	-40 °C ... +75 °C
---------------------	-------------------

Mechanical Data

Version	Metric/metric
Degree of protection (IP)	IP66
Material	Polyamide, Glass fibre reinforced
Silicone-free	Yes
Design	A
Width across flats	36 mm
Length	28 mm
Outer diameter	41 mm
External thread	M25
Thread size	M25
Thread length	10 mm
Thread pitch	1,5
Thread pitch 2	1,5
Internal thread	M32
Impact strength (IEC 60079)	7 J
Colour	Black
Weight	11 g
Weight	0.02 lb

M25-M32 Art. No. 109389

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



Ga = External thread

Gi = Internal thread

L = Thread length

SW = Width across flats

E = Width across corners

TL = Length

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.