

CMP-50sPXSS2K Art. No. 109445



- Cable gland for unarmoured cables and cables with wire-braid armouring
- Designed to prevent coldflow
- Internationally certified in accordance with IECEx, ATEX, UL and cCSAus

MY R. STAHL PXSS2KA



The Series PXSS2K metal Ex d and Ex e barrier cable glands are suitable for unarmoured cables or cables with wire-braid armouring. They are equipped with a compound barrier. They have a displacement seal for the outer cable sheath, combined with a double flood seal with integral protection.

Technical Data

Explosion Protection

Area of application	EAC India UL CCC Canada (CSA) TUV European Union (ATEX) IECEX UKEX
Ex version	Ex e & Ex d & Ex nR & Ex ta
Application range (zones)	1, 2, 20, 21, 22
IECEX gas certificate	IECEX CML 18.0182X
IECEX gas explosion protection	Ex db eb IIC Gb
IECEX dust certificate	IECEX CML 18.0182X
IECEX dust explosion protection	Ex ta IIIC Da
IECEX firedamp protection	Ex db I Mb
IECEX firedamp protection 2	Ex eb I Mb
IECEX restricted breathing certificate	IECEX CML 18.0182X
IECEX restricted breathing	Ex nR IIC Gc
ATEX gas certificate 2	CML18ATEX4317X
ATEX gas explosion protection	Ex II 2 G Ex db eb IIC Gb
ATEX dust explosion protection	Ex II 1 D Ex ta IIIC Da
ATEX firedamp protection	Ex I M2 Ex db I Mb
ATEX firedamp protection 2	Ex I M2 Ex eb I Mb
ATEX restricted breathing certificate	CML 18ATEX1325X
ATEX restricted breathing	Ex II 3 G Ex nR IIC Gc
Notes	The product certificates can be downloaded from the manufacturer's homepage (www.cmp-products.com)

Installation equipment and accessories

Cable gland with compound



CMP-50sPXSS2K Art. No. 109445


Ambient Conditions

Ambient temperature	-60 °C ... +85 °C
---------------------	-------------------

Mechanical Data

Version	50s
Strain relief	No
Degree of protection (IP)	IP66
Degree of protection note	IP67 and IP68 mounting according to the specifications of the manufacturer, CMP. The specified degrees of protection are only fulfilled if CMP installation accessories are used.
Degree of protection (IP) UL	IP66
Sealing material	SOLO LSF
Sealing ring material	Viton
Material	Nickel-plated brass
Silicone-free	Yes
Clamping range	29.5 – 38.2 mm
Armouring type	Unarmoured cable types
Clamping range	29.5 ... 38.2 mm
Max. number of cores	89
Construction type	BS 6121, IEC/EN 62444
Width across corners	60.5 mm
Width across flats	55 mm
Thread size	M50
Thread length	15 mm
Thread pitch	1,5
Thread standard	metric
Gland size	50s
Inner sheath	36.6 mm
Max. internal conduit diameter	36.9 mm
Outer sheath	29.5 ... 38.2 mm
Protrusion length	65.2 mm
Impact strength	20 J
PVC boot	PVC15
Lot size	1
Weight	660 g
Weight	1.46 lb

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



- A = Max. inner sheath
- G = Max. internal conduit diameter
- B = Outer sheath
- C = Thread size
- D = Width across corners
- D = Width across flats
- E = Thread length
- F = Protrusion length

Installation equipment and accessories

Cable gland with compound



CMP-50sPXSS2K Art. No. 109445

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.