

Lighting

Compact light fitting Emergency luminaire

With battery

6109/111-0101-160-0111-31-1850-K11 Art. No. 287811



- Suitable for wall, ceiling and suspended mounting
- Operating modes: Continuous mode, continuous mode with switchable emergency lighting
- With function and rated operating time test with optional DALI technology
- Large recognition range $d \geq 30$ m
- Emergency exit signs with suspended panel so that they can be read from both sides
- Lightweight, robust and compact design

MY R. STAHL 6109A



C-LUX 6109 series compact emergency luminaires can be used for emergency lighting, as well as for indication or escape route luminaires.

Technical Data

Explosion Protection

Area of application	European Union (ATEX) IECEX
Ex version	Yes
Application range (zones)	1, 2, 21, 22
IECEX gas certificate	IECEX IBE 19.0016
IECEX gas explosion protection	Ex db eb ib op is IIC T4 Gb
IECEX dust certificate	IECEX IBE 19.0016
IECEX dust explosion protection	Ex tb op is IIIC T100 °C Db
ATEX gas certificate	IBExU 19 ATEX 1072
ATEX gas explosion protection	Ex II 2 G Ex db eb ib op is IIC T4 Gb
ATEX dust certificate	IBExU 19 ATEX 1072
ATEX dust explosion protection	Ex II 2 D Ex tb op is IIIC T100 °C Db
Certificates and approvals	ATEX IECEX
Certificates	ATEX (IBE), IECEX (IBE), Polen (CNBOP)
Declaration of conformity	ATEX (EUK)

Electrical Data

Frequency range	50 – 60 Hz
Battery version	NiCd battery, gas-tight
Battery operating voltage	6 V
Battery capacity	2.2 Ah
Self-test function	Function and battery duration test
LED service life	L90B50 ≥ 100 h
AC operating voltage	100 ... 240 V
Control interface	without

Lighting Data

Lamp	LED
Luminous flux	0 lm
Operating time	1.5 / 3h emergency lighting operation

Lighting

Compact light fitting Emergency luminaire

With battery

6109/111-0101-160-0111-31-1850-K11 Art. No. 287811



Lighting Data

Emergency light output	25% – 3 h 50% – 1.5 h
------------------------	--------------------------

Ambient Conditions

Ambient temperature	-30°C ... +50°C Note: Through wiring Max. 3x16 A -30°C ... +60°C Note: Through wiring 2 Max. 3x10 A
---------------------	--

Mechanical Data

IP degree of protection (IEC 60598)	IP66 / IP67
Class	I
Enclosure material	Thermoset
Enclosure colour	Light grey (RAL 7035)
Cover material	Polycarbonate
Sealing material	Silicone
Silicone-free content	Without influence on paint wetting
Pane material	PMMA
Installed terminal strip	PE + N + L1 + L2 + L3 + L"
Max. solid connection terminals	6 mm ²
Max. finely stranded connection terminals	4 mm ²
Type of connection cable	Finely stranded Solid
Size	1
Width	185 mm
Height	240 mm
Length	440 mm
Impact strength (IEC 62262)	IK08
Disconnection of the luminaire	No
Weight	4 kg
Weight	8.82 lb

Components

Variant	EXIT – single-sided Single-sided
Threaded plate	Plastic
Ballast	6046/311-841-060 NLE standard
Through wiring	Loop in/loop out
Drilled holes	3 x M25
Cable glands and entries	2 x M25 Ø 7 ... 17 mm
Stopping plugs	2 x M25 x 1.5
Stopping plug material	Polyamide, black
Breather	without
Accessories	Provided

Lighting


Compact light fitting Emergency luminaire

With battery


6109/111-0101-160-0111-31-1850-K11 Art. No. 287811

STAHL

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



with escape sign



with mounting brackets


Lighting

Compact light fitting Emergency luminaire

With battery

6109/111-0101-160-0111-31-1850-K11 Art. No. 287811


STAHL



for rope/chain mounting

Accessories

Breather




Thread: M20 x 1.5 (1 piece); for installation in light fittings; made from stainless steel; without jam nut

Art. No.

323702

Thread: M25 x 1.5 (1 piece); for installation in light fittings; made from stainless steel; without jam nut


296608



M25 x 1.5 in order to avoid condensate formation

115738


Fastening set



for chain/rope assembly

Art. No.

275407



for wall mounting

275408

Light panel



Escape route double sided

Art. No.

275872



Escape route, down

274776

Lighting

Compact light fitting Emergency luminaire

With battery

6109/111-0101-160-0111-31-1850-K11 Art. No. 287811

STAHL

Light panel

Art. No.

	Escape route, up	274758
	Escape route, down double-sided	274780
	Escape route, up double-sided	274772
	Escape route, left	274757
	Escape route, right	274775
	Escape route left/right double-sided	274773
	Escape route stairs, down left	274777
	Escape route stairs, down right	274778
	Escape route stairs, down double-sided	274779
	Escape route stairs, up left	274759
	Escape route stairs, up right	274760
	Escape route stairs, up double-sided	274771
	EXIT	275514

Lighting

Compact light fitting Emergency luminaire


With battery

6109/111-0101-160-0111-31-1850-K11 Art. No. 287811

STAHL

Spare Parts

Battery set




NiCd battery, gas-tight; 2.2 Ah / 6 V

Art. No.

273190

Optic



Diffuser

Art. No.

274756

Diffusing lens



Deflection optics

Art. No.

274781

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.