

8118/121-807 Art. No. 133126



- Resistant Ex e enclosure, universally usable as connection or junction boxes and/or to safeguard electric distributors up to 6.3 A
- IP66 degree of protection
- With mantle terminals or with a combination of mantle terminals and miniature fuses (optional)

MY R. STAHL 8118A



R. STAHL Series 8118 junction boxes are equipped with 4, 5 or 8 mantle terminals depending on their design size. As an option, miniature fuses can still be installed in addition. Junction boxes are therefore also suitable for safeguarding. The robust enclosure made from glass fibre reinforced polyester resin can be equipped with plastic or metal cable glands.

Technical Data

Explosion Protection

Area of application	European Union (ATEX) IECEx
Application range (zones)	1, 2, 21, 22
IECEx gas certificate	IECEx PTB 06.0026
IECEx gas explosion protection	Ex eb IIC T6 / T5 Gb
IECEx dust certificate	IECEx PTB 06.0026
IECEx dust explosion protection	Ex tb IIIC T80 °C / T95 °C Db
ATEX gas explosion protection	II 2 G Ex eb IIC T6 / T5 Gb
ATEX dust explosion protection	II 2 D Ex tb IIIC T80 °C / T95 °C Db
Certificates	ATEX (PTB), Brazil (ULB), China (NEPSI), IECEx (PTB), India (PESO), Korea (KTL)
Ship approval	DNV
Explosion protection note	For product label, see area of application.

Electrical Data

AC rated operational voltage	750 V
Rated operational voltage AC	0 ... 750 V
Permissible rated operational current with 7 loaded terminals	For conductor cross-section of 1.5 mm²: 13 A For conductor cross-section of 2.5 mm²: 17 A For conductor cross-section of 4 mm²: 24 A For conductor cross-section of 6 mm²: 32 A
Permissible rated operational current with 6 loaded terminals	For conductor cross-section of 1.5 mm²: 14 A For conductor cross-section of 2.5 mm²: 18 A For conductor cross-section of 4 mm²: 25 A For conductor cross-section of 6 mm²: 33 A
Permissible rated operational current with 5 loaded terminals	For conductor cross-section of 1.5 mm²: 14 A For conductor cross-section of 2.5 mm²: 20 A For conductor cross-section of 4 mm²: 25 A For conductor cross-section of 6 mm²: 35 A

8118/121-807 Art. No. 133126

Electrical Data

Permissible rated operational current with ≤ 4 loaded terminals	For conductor cross-section of 1.5 mm²: 16 A For conductor cross-section of 2.5 mm²: 20 A For conductor cross-section of 4 mm²: 25 A For conductor cross-section of 6 mm²: 35 A
--	--

Ambient Conditions

Ambient temperature	-60 °C ... +40 °C (T6) -60 °C ... +55 °C (T5)
Ambient temperature	-76°F ... +104°F (T6) -76°F ... +131°F (T5)

Mechanical Data

Degree of protection IP (IEC 60529)	IP66
Enclosure material	Polyester resin, Glass fibre reinforced
Enclosure colour	Dark grey
Flammability according to	IEC/EN 60695 UL 94 ASTM D635
Silicone-free	No
Permissible number of conductors per clamping unit, solid	Mantle terminal, M8.5 x 1 Conductor cross-section 1.5 mm²: Number of conductors min. 2, max. 7 Conductor cross-section 2.5 mm²: Number of conductors min. 2, max. 5 Conductor cross-section 4 mm²: Number of conductors min. 2, max. 3 Conductor cross-section 6 mm²: Number of conductors min. 2, max. 2
Permissible number of conductors per clamping unit, finely stranded prepared, core end sleeve crimped	Mantle terminal M8.5 x 1 Conductor cross-section 1.5 mm²: Number of conductors min. 2, max. 5 Conductor cross-section 2.5 mm²: Number of conductors min. 2, max. 3 Conductor cross-section 4 mm²: Number of conductors min. 2, max. 5
Permissible number of conductors per clamping unit, finely stranded unprepared	Mantle terminal, M8.5 x 1 Conductor cross-section 1.5 mm²: Number of conductors min. 2, max. 5 Conductor cross-section 2.5 mm²: Number of conductors min. 2, max. 3 Conductor cross-section 4 mm²: Number of conductors min. 2, max. 5
Permissible number of conductors per clamping unit note	All conductors of a terminal must have the same cross section and be made of the same material.
Cover	Screw-on cover
Cover fixing type	M4 stainless steel screws, With captive screws
Width	115 mm
Width, inches	4.53 in
Height	115 mm
Height in inches	4.53 in
Depth	64 mm
Depth in inches	2.52 in
Packaging unit	1
Weight	600 g
Weight	1.32 lb

Mounting / Installation

Tightening torque of cover screw 1	1.4 N · m
Tightening torque of cover screw 1 lbf in	12.4 lbf in

8118/121-807 Art. No. 133126


Components

Entry 1	4 x 8161/7-M25-1707-LT (Provided separately)
Entry 1 type	Polyamide cable gland, black
Entry 1	M25 x 1.5
Entry 1 clamping range	7 – 17 mm
Entry 1 clamping range, inch	0.28 – 0.67 in
Metal entry possible 1	No
Entry 2	2 x 8290/3-M25 (Provided separately)
Entry 2 type	Polyamide stopping plug
Entry 2	M25 x 1.5
Metal entry possible 2	No
Entries installation options/side	Size 2: 6x M25 (A+B+C+D)
Type of terminals 1	8 x Mantle terminal 6 mm ²

Technical Drawings – Subject to Alterations





Eight terminals




"—" = marking for mounting options

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



Length L
Projection dimension for cable gland of Series 8161:
For M20: 25 to 31 [0.98 to 1.22]
For M25: 27 to 33 [1.06 to 1.3]
For M32: 32 to 39 [1.26 to 1.54]



8118/2.
Enclosure SZ 2

Accessories

Plastic cable gland



8161/7-M25-1707-LT, Ex e
Polyamide, M25 x 1,5 mm, 7 – 17 mm
Lot size 50 pieces

Art. No.




329693

8118/121-807 Art. No. 133126

Stopping plug


	8290/3-M25 Plastic, M25 x 1.5 Lot size 100 piece	Art. No. 285774
--	---	-----------------------------------

Brass plate with thread

	8118 SZ 2, plate 56 x 40 mm [2.2 x 1.57 inch] 2 x M20 x 1.5 with M4 PE connection (right) For installation in enclosure SZ 2 and SZ 3	Art. No. 244072
	8118 SZ 2, plate 56 x 40 mm [2.2 x 1.57 inch] 1 x M25 x 1.5 with M4 PE connection (left) For installation in enclosure SZ 2 and SZ 3	Art. No. 211341
	8118 SZ 3/B, plate 74 x 40 mm [2.91 x 1.57 inch] 2 x M20 x 1.5 with M4 PE connection (centre) For installation in enclosure SZ 2 and SZ 3	Art. No. 244075

Spare Parts

Angle

	Bracket 8118 SZ 2, for junction boxes, 4 x M25 For installation in enclosure SZ 2	Art. No. 202959
--	--	-----------------------------------

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.