# **Installation Equipment and Accessories**

Post-type bushing



### 8171/51-CB Art. No. 139215



- Means of supplying power to lead-in for Ex d enclosures
- Sealed to prevent propagation of flame on explosion and insulated from wall
- Versions with: split post connection, clamp connection, soldered connection
- · For voltages up to max. 1000 V and currents up to max. 630 A

## MY R. STAHL 8171A



The bushings are permitted to be used as current feeders in enclosures with type of protection "flameproof".

They are fitted puncture-proof and insulated into the enclosure wall.

Duct bolt is located in the middle of a ring nut and the parts are bonded with a high-quality, track resistant insulating material (epoxy resin) to form an inseparable unit.

For the connection points in the Ex e enclosure increased creepage paths and air gaps according to IEC/EN 60079-7 are valid.

The bushings have to be secured against self-loosening.

### **Technical Data**

Explosion Protection	
Ex version	Yes
Application range (zones)	1
	2
IECEx gas certificate	IECEx PTB 06.0080U
IECEx gas explosion protection	Ex de IIC Gb
ATEX gas certificate	PTB 00 ATEX 1066 U
ATEX gas explosion protection	🐼 II 2 G Ex de IIC Gb
Certificates	ATEX (PTB), China (CQST), IECEx (PTB)
Electrical Data	
Rated operational voltage AC	1000 V
Rated operational current	200 A
Ambient Conditions	
Ambient temperature	-55 °C +130 °C
Mechanical Data	
Feedthrough bolt material	Brass
Moulding material	Epoxy resin
Ex d connection terminal	Cheese head screw
Ex e connection terminal	Round terminal
Connection cross-section	70 mm <sup>2</sup>
Number of bolts	1
Width across flats	SW46
Thread size	M42
Thread pitch	1,5
Weight	292 g

R. STAHL Schaltgeräte GmbH | Am Bahnhof 30 | 74638 WALDENBURG

# **Installation Equipment and Accessories**

Post-type bushing




## 8171/51-CB Art. No. 139215

#### Mechanical Data

Weight	0.64 lb	
Mounting / Installation		
Tightening torque	50 Nm	

#### Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



8171/51-CB

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.