

8174/203-1203-33 Art. No. 139628



- Current lead-in for Ex d enclosures
- 1 to 72 conductors combined in one current lead-in
- Series: screw-in, plug-in
- For voltages up to max. 1000 V
- For size conductor up to 70 mm<sup>2</sup>

WebCode 8174A



The conductor bushings are used to provide the wire connection between „flameproof“ enclosures and „increased safety“ enclosures.

The conductors are potted with high-quality, creepage-resistant PU-resin and are thus insulated from the enclosure wall.

### Technical Data

#### Explosion Protection

Application range (zones)	1 2
IECEX gas certificate	IECEX PTB 06.0081U
IECEX gas explosion protection	Ex db IIC Gb
IECEX firedamp certificate	IECEX PTB 06.0081U
IECEX firedamp protection	Ex db I Mb
ATEX gas certificate	PTB 01 ATEX 1065 U
ATEX gas explosion protection	⊕ II 2 G Ex db IIC Gb
ATEX firedamp certificate	PTB 01 ATEX 1065 U
ATEX firedamp protection	⊕ I M2 Ex db I Mb
Certificates	ATEX (PTB), EAC (ENDCE), IECEX (PTB)

#### Ambient Conditions

Ambient temperature	-40 °C ... +110 °C
---------------------	--------------------


#### Mechanical Data

Socket diameter	ø 34
Ex d conductor length	1300 mm
Ex e conductor length	1300 mm
Min. conductor cross section	2.5 mm <sup>2</sup>
Number of core ends	12
Thread size	M42
Thread pitch	1,5
Cable colour	Black
Weight	1.15 kg
Weight	2.54 lb


8174/203-1203-33 Art. No. 139628

### Technical Drawings – Subject to Alterations


Strombelastbarkeit  
von Leitungen 2,5 mm<sup>2</sup> in M33 x 1,5 / ø 34



Current loading of  
2,5 mm<sup>2</sup> of cables in M33 x 1,5 / ø 34



Intensité du courant des câbles  
2,5 mm<sup>2</sup> dans M33 x 1,5 / ø 34



We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.