

# Safety barriers

## Single-channel safety barriers



9001/02-016-015-101 Art. No. 158669



- For the intrinsically safe operation of a wide range of devices, such as HART transmitters, solenoid valves, sensors, potential-free contacts and many more
- Compact and space-saving devices that are easy to install on a DIN rail
- Quick to install as barriers can be simultaneously snapped onto the rail and connected to PE

MY R. STAHL 9001A



The series 9001 INTRINSPAK single-channel safety barriers enable the intrinsically safe operation of virtually all field devices. The comprehensive portfolio and the combination of safety barriers cover a wide variety of signals. The devices are incredibly robust and require little space. The back-up fuse is a convenient feature as it is standardised for all variants.

### Technical Data

Explosion Protection	
Application range (zones)	2
Ex interface zone	0, 1, 2, 20, 21, 22
IECEX gas certificate	IECEX PTB 09.0001X
IECEX gas explosion protection	Ex ec [ia Ga] IIC T4 Gc
IECEX dust certificate	IECEX PTB 09.0001X
IECEX dust explosion protection	[Ex ia Da] IIIC
ATEX gas certificate	PTB 01 ATEX 2088 X
ATEX gas explosion protection	⊕ II 3 (1) G Ex ec [ia Ga] IIC T4 Gc
ATEX dust certificate	PTB 01 ATEX 2088 X
ATEX dust explosion protection	⊕ II (1) D [Ex ia Da] IIIC
FMus certificate	3011002
Marking FMus	NONINCENDIVE FOR, Class I, Div. 2, Groups A,B,C,D; T4; Class I, Zone 2, Group IIC T4 IS connections for Class I,II,III, Div. 1, Groups A,B,C,D,E,F,G; Class I, Zone 0, Groups IIC/IIB Hazardous location when inst. per doc. 90 016 11 31 1
Certificate ULus	E81680V1S3
Marking ULus	For use in Hazardous location, Class I, Div. 2, Groups A,B,C,D; T4 Providing IS circuits for Class I,II,III, GROUPS A,B,C,D,E,F,G; per doc. 90 016 11 31 3
Inmetro gas certificate	UL-BR 12.0353
Inmetro dust certificate	UL-BR 12.0353
Certificates	ATEX (PTB), Brazil (ULB), Canada (FM), China (NEPSI), IECEX (PTB), India (PESO), Japan (CML), Korea (KGS), USA (FM), USA (UL)
Declaration of conformity	ATEX (EUK), China (CCC)
Installation	in Zone 2, Division 2 and in safe areas
Further information	See relevant certificate and operating instructions

# Safety barriers

## Single-channel safety barriers



9001/02-016-015-101 Art. No. 158669

### Safety Data

Max. voltage $U_o$	1.6 V		
Max. current $I_o$	15 mA		
Max. power $P_o$	6 mW		
Max. permissible external capacity $C_o$ for IIC	100 $\mu$ F		
Max. permissible external inductance $L_o$ for IIC	160 mH		
Max. permissible external capacity $C_o$ for IIB	1000 $\mu$ F		
Max. permissible external inductance $L_o$ for IIB	560 mH		
Intrinsically safe limiting values Inductance $L_o$ /capacitance $C_o$	Jointly connectable inductance $L_o$ /capacitance $C_o$		
IIC	$L_o$ [mH]	20 mH	1 mH
	$C_o$ [ $\mu$ F]	21 $\mu$ F	37 $\mu$ F
IIB	$L_o$ [mH]	50 mH	1 mH
	$C_o$ [ $\mu$ F]	96 $\mu$ F	220 $\mu$ F

### Electrical Data

Number of channels	1		
Type of voltage	AC/DC		
Maximum resistance $R_{max}$	134 $\Omega$		
Minimum resistance $R_{min}$	120 $\Omega$		
Maximum output current $I_{max}$	5 mA		
Potential	alternating		
Transmission frequency channel 1	$\leq$ 50 kHz		
$I_{leak}$ leakage current for $U_n$	$\leq$ 10 $\mu$ A		

### Auxiliary Power

Nominal voltage	$\pm$ 0.7 V		
Power supply	Controlled		

### Output

Temperature influence	$\leq$ 0,25 %/10K		
-----------------------	-------------------	--	--

### Ambient Conditions

Ambient temperature	-20 °C ... 60 °C		
Ambient temperature	-4°F ... +140°F		
Storage temperature	-20 °C ... 75 °C		
Storage temperature	-4°F ... +167°F		
Maximum relative humidity	95% average, no condensation		

### Mechanical Data

Degree of protection (IP)	IP40		
Degree of protection note	according to IEC 60529		
Degree of protection (IP) terminals	IP20		
Enclosure material	Polyamide 6GF		
Number of connection terminals	4		
Connection cross section min.	1.5 mm <sup>2</sup>		
Connection cross-section max.	1.5 mm <sup>2</sup>		
Connection cross-section AWG	16 AWG		

9001/02-016-015-101 Art. No. 158669

### Mechanical Data

Type of connection cable	Finely stranded Solid
Width	103 mm
Width, inches	4.09 in
Length	12 mm
Length in inches	0.48 in
Mounting depth	72 mm
Mounting depth in inches	2.76 in
Weight	110 g
Weight	0.24 lb

### Mounting / Installation

Earthing connection cross-section	4 mm <sup>2</sup>
Earthing conductor cross-section AWG	12 AWG
Connection type	2 PA
Min. torque, Nm	0.5 N · m
Min. torque, lb/in	4.43 lb/in
Max. torque, Nm	0.6 N · m
Max. torque, lb/in	5.31 lb/in

### Technical Drawings – Subject to Alterations







Image F




Single-Channel Safety Barriers for Alternating Polarity


### Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



mounted on the NS 35/15 mounting rail



mounted on the NS 32 mounting rail with adaptor and clamping base made of moulded material



installed on mounting plate with adaptor

# Safety barriers


## Single-channel safety barriers




9001/02-016-015-101 Art. No. 158669

### Accessories


#### Terminal block

		Art. No.
	Phoenix Contact terminal block UT 4-PE	113057
	Phoenix Contact terminal block UT 6-PE	113058


#### Adaptor

		Art. No.
	The adaptor enables a safety barrier to be installed on a clamping base (Art. No. 165283) or mounting plate from a previous series.	158826

#### Clamping base, moulded material


		Art. No.
	Enables the safety barrier to be mounted on a G-rail. The safety barrier is mounted using the adaptor (Art. No. 158826).	165283

#### Fuse holder


		Art. No.
	The fuse holder is snapped onto the side of a safety barrier and can be equipped with up to five back-up fuses (replacement).	158834

### Spare Parts

#### Back-up fuse

		Art. No.
	For all series 9001, 9002 and 9004 safety barriers Packaging unit: 5 pieces	158964

#### Label carrier

		Art. No.
	Transparent cover for the label	158977

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.