



- Backlit text and graphics with dimming control
- Audible and visual alarms
- Custom made text

MY R. STAHL T4500A

The operator panels for TEF 4500 Commander Utility are very flexible in sizes and configurations. The panels are custom built and allow for use of text in several languages. With a dimmable backlight these are easy to read in daylight as well as at night. Several panels may be connected to the same network, more typical with non-critical applications. Alarms are provided with flashing LED's as well as a buzzer for audible alarms. Alarms are acknowledged and silenced by pushing the Alarm Acknowledge button.


APPLICATIONS:

Deck light control panel
 Floodlight control panel
 Helideck control panel
 Heating system control panel
 Pump control panel
 Status panel
 General control pane

Technical Data

Electrical Data	
DC supply voltage	24 V
Number of RS-485 interfaces	2
Auxiliary Power	
Auxiliary pwr nom. voltage DC	24 V
Diagnostics	
Communication	RS-485
Display	
Backlight	Dimmable LED
Mechanical Data	
Degree of protection (IP)	IP22
Enclosure material	Aluminium
Number of buttons	37
Size	3
Mounting cut-out width	260 mm
Mounting cut-out height	205 mm
Weight	100 g

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



A = 260 mm; B = 205 mm

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.