

Control and signalling devices

Control devices for panel mounting

Ex e

8003/111-009S-MS1 UL Art. No. 217911



- Flexible configuration thanks to pushbutton, mushroom push-button, mushroom stay-put button, mushroom stay-put button with key lock, key-operated button and key-operated switch
- Easy to install using a single hole
- Codable "latching", "spring return" and "key not removable" functions
- Spring clamp terminals with connection chamber

MY R. STAHL 8003A



R. STAHL Series 8003 switches and control buttons for panel mounting take on various switching functions in latching and spring return positions up to 6 A, which can be subsequently recoded. They are fully certified, explosion-protected equipment with an Ex e connection chamber. With the patented mounting mechanism, panel mounting with drilled holes or openings of 30.5 mm is quick and easy.

Compatible actuators are available for a comprehensive range of applications.

Technical Data

Explosion Protection

| | |
|---------------------------------|---|
| Area of application | European Union (ATEX) CE Code IECEX NEC® |
| Application range (zones) | 1, 2, 21, 22 |
| IECEX gas certificate | IECEX PTB 06.0065X |
| IECEX gas explosion protection | Ex db eb IIC T6 Gb |
| IECEX dust certificate | IECEX PTB 06.0065X |
| IECEX dust explosion protection | Ex tb IIIC T80 °C Db |
| ATEX gas certificate | PTB 02 ATEX 1057 X |
| ATEX gas explosion protection | ⊕ II 2 G Ex db eb IIC T6 Gb |
| ATEX dust certificate | PTB 02 ATEX 1057 X |
| ATEX dust explosion protection | ⊕ II 2 D Ex tb IIIC T80 °C Db |
| Certificates | ATEX (PTB), Canada (UL), China (CQST), IECEX (PTB), Korea (KGS), USA (UL) |
| Declaration of conformity | ATEX (EUK), ATEX (Simple apparatus), China (CCC) |
| Notes | Product label may vary. Series devices are labelled with ATEX, IECEX, NEC® and CE Code. |

Electrical Data

| | |
|--|----------------------------|
| AC rated operational voltage | 500 V |
| Rated operational current | 6 A |
| Rated operational current | 6 A |
| Switching capacity AC-12 | 500 V / 6 A / max. 3000 VA |
| Switching capacity AC-15 | 400 V / 6 A / max. 1250 VA |
| Switching capacity DC-13 | 110 V / 1 A / max. 110 W |
| Switching capacity DC-13 2 contact elements in series | 60 V/6 A |

Control and signalling devices

Control devices for panel mounting



Ex e

8003/111-009S-MS1 UL Art. No. 217911

Ambient Conditions

| | |
|--------------------------|--------------------|
| Ambient temperature | -55 °C ... 60 °C |
| Ambient temperature | -67 °F ... +140 °F |
| Ambient temperature NEC® | -55 °C ... +60 °C |
| Ambient temperature NEC® | -67 °F ... +140 °F |

Mechanical Data

| | |
|---------------------------------------|------------------------------------|
| Degree of protection (IP) (IEC 60529) | Reverse side IP65, front side IP66 |
| Enclosure material | Polyamide |
| Contact material | Silver-nickel |
| Silicone-free | No |
| Number of NCs | 1 |
| Number of NOs | 1 |
| Connection cross-section | 0.75 ... 1.5 mm ² |
| Connection cross-section AWG | 18 AWG ... 12 AWG |
| Mounting depth | 130 mm |
| Mounting depth in inches | 5.12 in |
| Service life, min. | 10 ⁵ operating cycles |
| Weight | 140 g |


Mounting / Installation

| | |
|--------------------------|--------------|
| Tightening torque | 3 N · m |
| Tightening torque lbf in | 26.55 lbf in |




Components

| | |
|--------------|--|
| Actuator | Mushroom stay-put button With key actuator EM-STOP MS1 |
| Entry 1 | 8161/7-M16-0902 |
| Entry 1 type | Polyamide cable gland, black |

Technical Drawings – Subject to Alterations



Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations




Control and signalling devices

Control devices for panel mounting




Ex e

8003/111-009S-MS1 UL Art. No. 217911




Punch pattern



Cut-out with/without additional designation plate

Accessories

Actuators



| | Art. No. |
|---|----------|
| Mushroom stay-put button with EM-STOP key | 261755 |

Closing part



| | Art. No. |
|---|----------|
| 8602C3-733-B for closing unused holes in cover, dia. 30.5 mm, NBR | 244306 |
| 8602C3-733-S for closing unused holes in cover, dia. 30.5 mm, silicone | 244307 |

Spare Parts

Label holder



| | Art. No. |
|--|----------|
| Label holder, size 1, without insert disc Labelling: 1-line can be installed in dia. 30.5 mm drilled holes for actuators | 155632 |



| | |
|--|--------|
| Label holder, size 2, without insert disc Labelling: 1- or 2-line can be installed in dia. 30.5 mm drilled holes for actuators | 155687 |
|--|--------|



| | |
|--|--------|
| Label holder, size 3, without insert disc Labelling: 1-, 2- or 3-line can be installed in dia. 30.5 mm drilled holes for actuators | 155844 |
|--|--------|

Label, yellow, general



| | Art. No. |
|-----------------------------|----------|
| for Ø 39 actuator (EM-STOP) | 223571 |






Control and signalling devices

Control devices for panel mounting



Ex e

8003/111-009S-MS1 UL Art. No. 217911

| Protective collar | | Art. No. |
|--|--|----------|
|  | 8602A0751 metal for pushbutton/selector switch/mushroom stay-put button with key lock/mushroom stay-put button/mushroom pushbutton dia. 39 BG001, BG003, BG005, BG008, BG009, BG010, BG012 | 155326 |
| Spare key | | Art. No. |
|  | Closing MS1 | 107109 |
| Insert discs for label holder | | Art. No. |
|  | One-line Plain Material: PVC Colour: White Self-adhesive | 238271 |
|  | Two-line Plain Material: PVC Colour: White Self-adhesive | 238272 |
|  | Three-line Plain Material: PVC Colour: White Self-adhesive | 238273 |

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.