


8118/122-199-K0125 Art. No. 220336



- Compact, impact-resistant enclosure, also available in versions with integrated metal bracket for optimised installation of cable glands
- Customer-specific equipping with terminals, cable glands and miniature fuses
- IP66 degree of protection

MY R. STAHL 8118B



R. STAHL Series 8118 terminal boxes are equipped, in accordance with customer specifications, with various series terminals and cable glands made from plastic or metal, if required also with miniature fuses. They are available in 3 design sizes and are made from glass fibre reinforced polyester resin.

### Technical Data

#### Explosion Protection

Scope of validity	European Union (ATEX) IECEX
Application range (zones)	1 2 21 22
IECEX gas certificate	IECEX PTB 06.0026
IECEX gas explosion protection	Ex eb IIC T6 / T5 Gb
IECEX dust certificate	IECEX PTB 06.0026
IECEX dust explosion protection	Ex tb IIIC T80 °C / T95 °C Db
ATEX gas certificate	PTB 99 ATEX 3103
ATEX gas explosion protection	⊕ II 2 G Ex eb IIC T6 / T5 Gb
ATEX dust certificate	PTB 99 ATEX 3103
ATEX dust explosion protection	⊕ II 2 D Ex tb IIIC T80 °C / T95 °C Db
Certificates	ATEX (PTB), IECEX (PTB), India (PESO), Korea (KTL)
Explosion protection note	For product label, see scope of validity.

#### Electrical Data

Rated operational voltage AC	690 V
Max. number of conductors for conductor cross-section 1.5 mm <sup>2</sup>	At 3 A: 26 <sup>*)</sup> At 6 A: 26 <sup>*)</sup> At 10 A: 26 <sup>*)</sup> At 16 A: 6 <sup>*)</sup>
Max. number of conductors for conductor cross-section 2.5 mm <sup>2</sup>	At 3 A: Any At 6 A: 26 <sup>*)</sup> At 10 A: 26 <sup>*)</sup> At 16 A: 14 <sup>*)</sup> At 20 A: 6 <sup>*)</sup>

8118/122-199-K0125 Art. No. 220336

### Electrical Data

Max. number of conductors for conductor cross-section 4 mm <sup>2</sup>	At 3 A: Any At 6 A: Any At 10 A: 22 <sup>*)</sup> At 16 A: 22 <sup>*)</sup> At 20 A: 22 <sup>*)</sup> At 25 A: 8 <sup>*)</sup>
Max. number of conductors for conductor cross-section 6 mm <sup>2</sup>	At 3 A: Any At 6 A: Any At 10 A: Any At 16 A: 20 <sup>*)</sup> At 20 A: 20 <sup>*)</sup> At 25 A: 20 <sup>*)</sup> At 35 A: 4 <sup>*)</sup>
Max. number of conductors note	Each inserted conductor and each internal connection conductor counts as a conductor. Jumpers and protective conductors do not count.  <sup>*)</sup> When using these values, simultaneity factors or load factors must be taken into account according to IEC 61439. A mixed assembly with electrical circuits of different cross sections and currents is possible with proportional utilisation of the different tables of values.

### Ambient Conditions

Ambient temperature	-20 °C ... +40 °C (T6) -20 °C ... +55 °C (T5)
Ambient temperature	-4°F ... +104°F (T6) -4°F ... +131°F (T5)

### Mechanical Data

Degree of protection IP (IEC 60529)	IP66
Enclosure material	Polyester resin, Glass fibre reinforced
Enclosure colour	Dark grey
Flammability according to	IEC/EN 60695 UL 94 ASTM D635
Silicone-free	No
Cover	Screw-on cover
Cover fixing type	M4 stainless steel screws, With captive screws
Width	115 mm
Width, inches	4.53 in
Height	115 mm
Height, inches	4.53 in
Depth	64 mm
Depth, inches	2.52 in
Packaging unit	1
Weight	580 g
Weight	1.28 lb

### Mounting / Installation

Tightening torque of cover screw 1	1.4 Nm
Tightening torque of cover screw 1 lbf in	12.4 lbf in

### Components


Entry 1	1 x 8161/7-M25-1707
Entry 1 type	Polyamide cable gland, black

8118/122-199-K0125 Art. No. 220336

### Components



Entry 1	M25 x 1.5
Entry 1 terminal area	7 – 17 mm
Entry 1 clamping range, inch	0.28 – 0.67 in
Metal entry possible 1	No
Entry 2	1 x HSK-K-MZ-ExM25x1.5 Union nut in aluminum, black
Entry 2 type	Polyamide cable gland, black
Entry 2	M25 x 1.5
Entry 2 terminal area	13 – 18 mm
Entry 2 clamping range, inch	0.51 – 0.71 in
Metal entry possible 2	No
Entries installation options/side	According to order
Terminal rail	35 x 50 mm (1x)
Terminal rail	1,38 x 3,94 " (1x)
Type of terminals 1	4 x Phoenix UT 4 2-conductor, 4 mm <sup>2</sup> , grey
Type of terminals PE 1	1 x Phoenix UT 4-PE 2-conductor, 4 mm <sup>2</sup> , green-yellow
	For connection cross-sections, see the manufacturer's data sheet

### Technical Drawings – Subject to Alterations



"—" = marking for mounting options

### Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



Length L  
 Projection dimension for cable gland of Series 8161:  
 For M20: 25 to 31 [0.98 to 1.22]  
 For M25: 27 to 33 [1.06 to 1.3]  
 For M32: 32 to 39 [1.26 to 1.54]  
 Projection dimension for cable gland with strain relief  
 of Series HSK-K-MZ  
 For M25: 41 [1.61]



8118/.2.  
Enclosure SZ 2

### Accessories

#### Cable gland made of plastic

	8161/7-M25-1707, Ex e Plastic, M25 x 1.5, cable outer diameter 7 to 17 mm Lot size 50 pieces	<b>Art. No.</b> 239157
--	--	---------------------------

8118/122-199-K0125 Art. No. 220336

Terminal block		Art. No.
	Phoenix Contact terminal block UT 4	113045
	Phoenix Contact terminal block UT 4-PE	113057

Brass plate with thread		Art. No.
	8118 SZ 1, plate 37 x 30 mm [1.46 x 1.18 inch] 1 x M20 x 1.5 with M4 PE connection (left) Can be installed in enclosures of SZ 1, SZ 2 and SZ 3	168913
	8118 SZ 1, plate 37 x 30 mm [1.46 x 1.18 inch] 1 x M20 x 1.5 with M4 PE connection (right) Can be installed in enclosures of SZ 1, SZ 2 and SZ 3	168914
	8118 SZ 2, plate 56 x 40 mm [2.2 x 1.57 inch] 2 x M20 x 1.5 with M4 PE connection (right) For installation in enclosure SZ 2 and SZ 3	244072
	8118 SZ 2, plate 56 x 40 mm [2.2 x 1.57 inch] 1 x M25 x 1.5 with M4 PE connection (left) For installation in enclosure SZ 2 and SZ 3	211341
	8118 SZ 3, plate 74 x 40 mm [2.91 x 1.57 inch] 2 x M20 x 1.5 with M4 PE connection (centre) For installation in enclosure SZ 2 and SZ 3	168915
	8118 SZ 3/B, plate 74 x 40 mm [2.91 x 1.57 inch] 2 x M20 x 1.5 with M4 PE connection (centre) For installation in enclosure SZ 2 and SZ 3	244075
	8118 SZ 3, plate 74 x 40 mm [2.91 x 1.57 inch] 1 x M20 x 1.5 + 1 x M10 with M4 PE connection (centre) For installation in enclosure SZ 2 and SZ 3	211342
	8118 SZ 3, plate 74 x 40 mm [2.91 x 1.57 inch] 2 x M25 x 1.5 with M4 PE connection (centre) For installation in enclosure SZ 2 and SZ 3	168916
	8118 SZ 3, plate 74 x 40 mm [2.91 x 1.57 inch] 1 x M25 x 1.5 + 1 x M10 with M4 PE connection (centre) For installation in enclosure SZ 2 and SZ 3	211343

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.