

CMP-747-DA-T2-5 Art. No. 230107



- Metal Ex d and Ex e stopping plugs
- Wide selection of thread types and sizes
- Operating temperature range -60 °C to +200 °C
- Global certification, IECEx, ATEX, cCSAus and UL

MY R. STAHL 747DA



The Series 747 metal Ex d and Ex e stopping plugs with hexagon socket and without a projecting head make it possible to temporarily or permanently seal unused drilled holes. There is a wide selection of different thread sizes and types available for this. They have global certification according to IECEx, ATEX, UL and cCSAus.

### Technical Data

#### Explosion Protection

Application range (zones)	1, 2, 20, 21, 22
IECEX gas certificate	IECEX CML 18.0177X
IECEX gas explosion protection	Ex db IIC Gb
IECEX dust certificate	IECEX CML 18.0177X
IECEX dust explosion protection	Ex ta IIIC Da
IECEX firedamp protection	Ex db I Mb
IECEX firedamp protection 2	Ex eb I Mb
ATEX gas explosion protection	⊕ II 2 G Ex db IIC Gb
ATEX dust explosion protection	⊕ II 1 D Ex ta IIIC Da
ATEX firedamp protection	⊕ I M2 Ex db I Mb
ATEX firedamp protection 2	⊕ I M2 Ex eb I Mb
Notes	The product certificates can be downloaded from the manufacturer's homepage ( <a href="http://www.cmp-products.com">www.cmp-products.com</a> )

#### Ambient Conditions

Ambient temperature	-60 °C ... +200 °C
---------------------	--------------------

#### Mechanical Data

Degree of protection (IP)	IP66
Material	Nickel-plated brass
Silicone-free	Yes
Drive	Hexagon socket
Dimension b	6.4 mm
Dimension d	18 mm
Outer diameter	26.9 mm
Thread size	NPT3/4
Thread length	20.2 mm
Thread pitch	1,8143
Impact strength (IEC 62262)	IK10

# Installation equipment and accessories

## Stopping plug Flush-mounted




CMP-747-DA-T2-5 Art. No. 230107

### Mechanical Data

Packaging unit	1
Weight	107 g
Weight	0.24 lb

### Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



A = Thread size  
B = Length  
L = Thread length  
d = Dimension d  
b = Dimension b  
D = Outer diameter  
SW = Hexagon socket width across flats

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.