

CMP-63sA2FRC Art. No. 243633



- Ex d and Ex e cable gland for all unarmoured cables and cables with wire-braid armouring in flexible conduits
- Outer cable sheath sealed by an explosion-protected displacement seal
- Globally certified in accordance with IECEx, ATEX and CSA

MY R. STAHL A2FRCA



Series A2FRC metal Ex d and Ex e cable glands are designed for all types of unarmoured cables and cables with wire-braid armouring which are installed in flexible or rigid conduits. Installation is incredibly easy thanks to a connector that can be rotated freely. The cable glands are designed to prevent cold flow.

Technical Data

Explosion Protection

Ex version	Ex e & Ex d & Ex nR & Ex ta
Application range (zones)	1 2 20 21 22
IECEX gas certificate	IECEX CML 18.0179X
IECEX gas explosion protection	Ex db IIC Gb
IECEX dust certificate	IECEX CML 18.0179X
IECEX dust explosion protection	Ex ta IIIC Da
IECEX restricted breathing certificate	IECEX CML 18.0179X
IECEX restricted breathing	Ex nR IIC Gc
ATEX gas certificate	CML 18ATEX1321X
ATEX gas explosion protection	⊕ II 2 G Ex db IIC Gb
ATEX dust certificate	CML 18ATEX1321X
ATEX dust explosion protection	⊕ II 1 D Ex ta IIIC Da
ATEX restricted breathing certificate	CML 18ATEX4313X
ATEX restricted breathing	⊕ II 3 G Ex nR IIC Gc
Notes	The product certificates can be downloaded from the manufacturer's homepage (www.cmp-products.com)

Mechanical Data


Version	63s
Strain relief	No
Degree of protection (IP)	IP66
Degree of protection note	Mounting in accordance with the specifications of the manufacturer, CMP
Sealing material	SOLO LSF
Material	Nickel-plated brass
Silicone-free	Yes

CMP-63sA2FRC Art. No. 243633

Mechanical Data

Clamping range	41.50-49.9 mm
Armouring type	Unarmoured cable types
Armouring type 2	Cable with protective braiding
Clamping range	41.5 ... 49.9 mm
Construction type	BS 6121, IEC/EN 62444
Width across corners	77.6 mm
Width across flats	70.5 mm
Thread size	M63
Thread length	15 mm
Thread pitch	1,5
Thread standard	metric
Gland size	63s
Inner sheath	41.5 ... 49.9 mm
Inner conduit thread	M63
Protrusion length	58.4 mm
Impact strength	20 J
PVC boot	PVC21
Lot size	1
Weight	720 g
Weight	1.59 lb

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



- A = Inner sheath
- C = Thread size
- D = Width across corners
- D = Width across flats
- E = Thread length
- F = Protrusion length
- G = Inner conduit thread

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.