


CMP-75PX2KREX Art. No. 246658



- Improved reliability: Flood seal with integral protection, controlled outer load retention seal, over-rotation protection
- "RapidEx" compound barrier for simple installation and increased reliability
- Internationally certified in accordance with IECEx, ATEX and cCSAus, EMC-tested

MY R. STAHL PX2KB



The Series PX2K REX metal Ex d and Ex e barrier cable glands are suitable for cables with SWA, wire-braid and tape armouring made of steel and aluminium. They are sealed by means of a liquid compound barrier ("RapidEx"), which reduces the amount of time, costs and risks involved in installation and offers increased reliability. They have a multifunctional holder for the armouring and various seals. They are also EMC-tested.

Technical Data

Explosion Protection	
Ex version	Ex e & Ex d & Ex nR & Ex ta
Application range (zones)	1, 2, 20, 21, 22
IECEx gas certificate	IECEx CML 18.0182X
IECEx gas explosion protection	Ex db eb IIC Gb
IECEx dust certificate	IECEx CML 18.0182X
IECEx dust explosion protection	Ex ta IIIC Da
IECEx firedamp certificate	IECEx CML 18.0182X
IECEx firedamp protection	Ex db I Mb
IECEx firedamp protection 2	Ex eb I Mb
IECEx restricted breathing certificate	IECEx CML 18.0182X
IECEx restricted breathing	Ex nR IIC Gc
ATEX gas certificate	CML18ATEX1325X
ATEX gas certificate 2	CML18ATEX4317X
ATEX gas explosion protection	Ex II 2 G Ex db eb IIC Gb
ATEX dust certificate	CML18ATEX1325X
ATEX dust explosion protection	Ex II 1 D Ex ta IIIC Da
ATEX firedamp certificate	CML18ATEX1325X
ATEX firedamp protection	Ex I M2 Ex db I Mb
ATEX firedamp protection 2	Ex I M2 Ex eb I Mb
ATEX restricted breathing certificate	CML18ATEX1325X
ATEX restricted breathing	Ex II 3 G Ex nR IIC Gc
Notes	The product certificates can be downloaded from the manufacturer's homepage (www.cmp-products.com)
Ambient Conditions	
Ambient temperature	-60 °C ... +85 °C


CMP-75PX2KREX Art. No. 246658

Mechanical Data

Version	75
Strain relief	No
Degree of protection (IP)	IP66
Degree of protection note	IP67 and IP68 mounting according to the specifications of the manufacturer, CMP. The specified degrees of protection are only fulfilled if CMP installation accessories are used.
Degree of protection (IP) UL	IP66
Sealing material	SOLO LSF
Material	Nickel-plated brass
Silicone-free	Yes
Halogen-free	Yes
Number of cables	1
Clamping range	66.7 – 78.4 mm
Armouring type	All armouring
Armouring type 2	Without lead sheath
Armouring type 3	With barrier seal
Clamping range	66.7 ... 78.4 mm
Max. number of cores	140
Construction type	BS 6121, IEC/EN 62444
Width across corners	110 mm
Width across flats	100 mm
Thread size	M75
Thread length	15 mm
Thread pitch	1,5
Thread standard	metric
Gland size	75
Grooved cone	0.6 ... 1.6 mm
Stepped cone	2.5 ... 3 mm
Inner sheath	64.2 mm
Max. internal conduit diameter	0 mm
Min. inner conduit diameter	0 mm
Outer sheath	66.7 ... 78.4 mm
Min. outer conduit diameter	0 mm
Max. external conduit diameter	0 mm
Protrusion length	88.3 mm
Impact strength (IEC 60079)	7 J
Impact strength	20 J
PVC boot	PVC30
Lot size	1
Weight	2.54 kg
Weight	5.6 lb

CMP-75PX2KREX Art. No. 246658

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



A = Max. inner sheath
G = Max. internal conduit diameter
B = Outer sheath
C = Thread size
D = Width across corners
D = Width across flats
E = Thread length
F = Protrusion length

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.