

IDM161-BT-ex Art. No. 249910



- Wireless Bluetooth scanner for all 1D barcodes
- Certified acc. to ATEX and IECEx for zones 1, 2, 21, 22
- Compatible with R. STAHL's SHARK, MANTA, EAGLE and RAPTOR HMI device platforms

MY R. STAHL IDMEXA



R. STAHL's IDM161-BT-ex barcode scanners are ATEX and IECEx certified for hazardous zones 1, 2, 21 and 22. They read all common 1D barcodes and confirm the reading process acoustically with a beep, visually with LED and with vibration. These explosion-protected HMI devices are all-round designed to meet industrial requirements: their compact enclosure with IP65 is extremely robust - it can withstand up to 50 drops onto concrete from a height of 2 m. The scanner transmits the data wirelessly via Bluetooth.

Technical Data

General

Technology	Peripherals
Special version	Bluetooth wireless scanner
Version	Linear imager scanner
Barcode types	one-dimensional 1D (barcode)
Base loading station	IDMx61-BT-Base-Z1 IDMx61-BT-Base IDMx61-Base
WebCode	IDMEXA

Explosion Protection

Ex version	Yes
Application range (zones)	1 2 21 22
Scope	EU (CE / ATEX) International (IECEx)
IECEx gas certificate	IBExU16ATEX1002
ATEX gas certificate	IECEx IBE 16.0002
IECEx gas explosion protection	Ex ib IIC T4 Gb
IECEx dust explosion protection	Ex ib IIIC T135°C Db
ATEX gas explosion protection	II 2 G Ex ib IIC T4 Gb
ATEX dust explosion protection	II 2 D Ex ib IIIC T135°C Db

Electrical Data

Rated operational voltage DC	3.6 V
Power consumption DC	330 mA (stand-by 80 / 130 mA; peak 500 mA)
Interfaces	Interface support (via supply module): RS-232 / RS-422 / USB

IDM161-BT-ex Art. No. 249910

Electrical Data

Battery power	approx. 60 scans when fully loaded
Bluetooth	Yes
Bluetooth function	Bluetooth V2.1 EDR, Class 2
Bluetooth range	approx. 30 m
Bluetooth frequency	2.4 ... 2.4835 GHz (ISM band)
Battery	Lithium ion battery 3.6 V; 2250 mAh or 1500 mAh
Light source	Visible red light, 630nm
Scan frequency	500 Hz
Reader distance	20 ... 850 mm
Code resolution	approx. ≥ 0.076 mm (depending on code)
Resistance to light interference	100 000 lx
Status LED	optical: 2x LED (operating status / read confirmation) acoustic: beeper / buzzer (can be switched off) vibration

Auxiliary Power

Power supply	Via battery
--------------	-------------

Ambient Conditions

Ambient temperature	-20°C ... +50°C
Storage temperature	-30°C ... +70°C
Relative humidity	± 95 % , non-condensing
Shock resistance	50 drops from a height of 2 m onto a concrete surface

Mechanical Data

Front enclosure protection type (IP)	IP65
Rear enclosure protection type (IP)	IP65
Enclosure material	Plastic
Connection cable	at ReaderBox-054-* VB-IDMx6x-Base-RS232-SR-1.8m-Z1 at VM125-ex-RS232-* VB-IDMx6x-Base-VM-RS232-1.8m-Z1 at VM125-ex-USB-* VB-IDMx6x-Base-VM-USB-1.8m-Z1
Width	104 mm
Height	185 mm
Depth	76 mm
Dimensions (WxHxD)	104 mm x 185 mm x 76 mm
Weight	260 g
Weight	0.57 lb

Accessories

Adapter Cable

	Art. No.
VB-IDMx6x-SOCKET-RS232-0.5m Adapter cable for IDMx6x scanner, display xx8 <--> IDMx6x connection cable, open ends to binder coupling for interface RSi-232 (xx8), cable length: 0.5 m straight	254452

IDM161-BT-ex Art. No. 249910

Base stations scanner		Art. No.
IDMx61-Base-A Base station for handheld scanner IDMx61-BT, no Bluetooth, Non-Ex, wireless loading station, loading in safe area		275761
IDMx61-Base-A Base station for handheld scanner IDMx61-BT, no Bluetooth, Non-Ex, wireless loading station, loading in safe area		275761
IDMx61-BT-Base-A Base station for handheld scanner IDMx61-BT, Bluetooth, Non-Ex, wireless access and loading station, Bluetooth, loading in safe area		275760
IDMx61-BT-Base-A-Z1 Base station for handheld scanner IDMx61-BT, Bluetooth, zone 1, wireless access and loading station, Bluetooth, loading in zone 1		275759
		310747
		310746
Battery		Art. No.
IDMx6x-BT-ex-LionX Replacement battery (Li ions) for IDMx6x-BT-ex		283128

IDM161-BT-ex Art. No. 249910

Connection Cable	Art. No.
VB-IDM160-RS232-SR-1.8m Connection cable for IDM160, connection to ReaderBox or SHARK xx8-RSi, interface RS-232, Ex i 5.6 V cable length 1.8 m, straight, Binder plug	224085
VB-IDM160-RS232-SR-3.6m Connection cable for IDM160, connection to ReaderBox or SHARK xx8-RSi, interface RS-232, Ex i 5.6 V cable length 3.6 m, coiled, Binder plug	224086
VB-IDMx60-RS232-1.8m Connection cable for IDM160 / IDM260, connection to VM125-ex-*, interface RS-232, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug	224081
VB-IDMx60-RS232-3.6m Connection cable for IDM160 / IDM260, connection to VM125-ex-*, interface RS-232, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug	224082
VB-IDMx60-USB-1.8m Connection cable for IDM160, connection to VM125-ex-*, interface USB, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug	224083
VB-IDMx60-USB-3.6m Connection cable for IDM160, connection to VM125-ex-*, interface USB, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug	224084
VB-IDMx6x-Base-RS232-SR-1.8m-Z1 Connection cable for base loading station IDM*-Z1, connection to ReaderBox or SHARK xx8-RSi, interface RS-232, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug	224102
VB-IDMx6x-Base-RS232-SR-3.6m-Z1 Connection cable for base loading station IDM*-Z1, connection to ReaderBox or SHARK xx8-RSi, interface RS-232, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug	224103
VB-IDMx6x-Base-VM-RS232-1.8m-Z1 Connection cable for base loading station IDM*-Z1, connection to VM125-ex-*, interface RS-232, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug	224100
VB-IDMx6x-Base-VM-RS232-3.6m-Z1 Connection cable for base loading station IDM*-Z1, connection to VM125-ex-*, interface RS-232, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug	224101
VB-IDMx6x-Base-VM-USB-1.8m-Z1 Connection cable for base loading station IDM*-Z1, connection to VM125-ex-*, interface USB, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug	224104
VB-IDMx6x-Base-VM-USB-3.6m-Z1 Connection cable for base loading station IDM*-Z1, connection to VM125-ex-*, interface USB, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug	224105

IDM161-BT-ex Art. No. 249910

Connection Cable Extension		Art. No.
	VB-IDMx6x-EXT-3.0m-Z1 Extension cable for IDMx6x zone 1, cable length 3 m, straight	265948
	VB-IDMx6x-EXT-3.0m-Z1-spiral Extension cable for IDMx6x zone 1, cable length 3 m, coiled	263908
	VB-IDMx6x-EXT-6m-Z1 Extension cable for IDMx6x zone 1, cable length: 6 m, straight	224108
	VB-IDMx6x-EXT-6.0m-Z1-spiral Extension cable for IDMx6x zone 1, cable length 6 m, coiled	265949
Power supply		Art. No.
	DSP-IDMx6x-DC5V Power supply for non-ex base loading station	224095
Tripod		Art. No.
	IDMx6x-tripod Tripod for IDMx6x, material: ABS (acrylonitrile-butadiene-styrene)	224106

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.