

IDM264-Z1 Art. No. 310744



- Certified acc. to ATEX and IECEx for hazardous Zones 1, 2, 21, 22
- Wired or wireless Bluetooth scanners
- 1D / 2D barcodes, stacked codes
- Scanner compatible with R. STAHL's SHARK, MANTA, EAGLE and RAPTOR HMI device platforms

MY R. STAHL IDMEXA



R. STAHL's IDM barcode scanners are ATEX and IECEx certified for hazardous zones 1, 2, 21 and 22.

Depending on the scanner, all common 1D / 2D barcodes and stacked codes can be read. The reading process is confirmed acoustically with a beep, visually with LED and with vibration. The explosion-protected HMI devices are all-round designed to meet industrial requirements: their compact enclosure with IP65 is extremely robust - it can withstand up to 50 drops onto concrete from a height of 2 m.

The wired scanners support all common cable interfaces, and, when required, the cables can be replaced without the need for any tools. The wireless Bluetooth scanners transmit all data via Bluetooth.

Technical Data

General	
Special version	wired handheld scanner
Version	two-dimensional imager scanner
Barcode types	one- and two-dimensional 1D and 2D (barcode and stacked code)
WebCode	IDMEXA
Explosion Protection	
Ex version	Yes
Application range (zones)	1 2 21 22
Scope	EU (CE / ATEX) International (IECEx)
IECEx gas certificate	IBExU16ATEX1002
ATEX gas certificate	IECEx IBE 16.0002
Electrical Data	
Rated operational voltage DC	4.9 V
Light source	Visible red light, 630nm
Resistance to light interference	100 000 lx
Auxiliary Power	
Power supply	Via supply module
Ambient Conditions	
Ambient temperature	-20°C ... +50°C
Storage temperature	-30°C ... +70°C

IDM264-Z1 Art. No. 310744

Ambient Conditions

Relative humidity	±95 % , non-condensing
Shock resistance	50 drops from a height of 2 m onto a concrete surface

Mechanical Data

Front enclosure protection type (IP)	IP65
Rear enclosure protection type (IP)	IP65
Enclosure material	Plastic
Width	104 mm
Height	185 mm
Depth	76 mm
Dimensions (WxHxD)	104 mm x 185 mm x 76 mm
Weight	200 g
Weight	0.44 lb

Accessories

Adapter Cable

Art. No.

VB-IDMx6x-SOCKET-RS232-0.5m Adapter cable for IDMx6x scanner, display xx8 <--> IDMx6x connection cable, open ends to binder coupling for interface RSi-232 (xx8), cable length: 0.5 m straight	254452
--	--------

Base stations scanner

Art. No.

IDMx61-Base-A Base station for handheld scanner IDMx61-BT, no Bluetooth, Non-Ex, wireless loading station, loading in safe area	275761
	310747
	310746

Battery

Art. No.

IDMx6x-BT-ex-LionX Replacement battery (Li ions) for IDMx6x-BT-ex	283128
---	--------

IDM264-Z1 Art. No. 310744

Connection Cable	Art. No.
VB-IDM160-RS232-SR-1.8m Connection cable for IDM160, connection to ReaderBox or SHARK xx8-RSi, interface RS-232, Ex i 5.6 V cable length 1.8 m, straight, Binder plug	224085
VB-IDM160-RS232-SR-3.6m Connection cable for IDM160, connection to ReaderBox or SHARK xx8-RSi, interface RS-232, Ex i 5.6 V cable length 3.6 m, coiled, Binder plug	224086
VB-IDMx60-RS232-1.8m Connection cable for IDM160 / IDM260, connection to VM125-ex-*, interface RS-232, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug	224081
VB-IDMx60-RS232-3.6m Connection cable for IDM160 / IDM260, connection to VM125-ex-*, interface RS-232, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug	224082
VB-IDMx60-USB-1.8m Connection cable for IDM160, connection to VM125-ex-*, interface USB, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug	224083
VB-IDMx60-USB-3.6m Connection cable for IDM160, connection to VM125-ex-*, interface USB, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug	224084
VB-IDMx6x-Base-RS232-SR-1.8m-Z1 Connection cable for base loading station IDM*-Z1, connection to ReaderBox or SHARK xx8-RSi, interface RS-232, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug	224102
VB-IDMx6x-Base-RS232-SR-3.6m-Z1 Connection cable for base loading station IDM*-Z1, connection to ReaderBox or SHARK xx8-RSi, interface RS-232, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug	224103
VB-IDMx6x-Base-VM-RS232-1.8m-Z1 Connection cable for base loading station IDM*-Z1, connection to VM125-ex-*, interface RS-232, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug	224100
VB-IDMx6x-Base-VM-RS232-3.6m-Z1 Connection cable for base loading station IDM*-Z1, connection to VM125-ex-*, interface RS-232, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug	224101
VB-IDMx6x-Base-VM-USB-1.8m-Z1 Connection cable for base loading station IDM*-Z1, connection to VM125-ex-*, interface USB, Ex i 5.6 V, cable length 1.8 m, straight, Binder plug	224104
VB-IDMx6x-Base-VM-USB-3.6m-Z1 Connection cable for base loading station IDM*-Z1, connection to VM125-ex-*, interface USB, Ex i 5.6 V, cable length 3.6 m, coiled, Binder plug	224105

IDM264-Z1 Art. No. 310744

Connection Cable Extension		Art. No.
	VB-IDMx6x-EXT-3.0m-Z1 Extension cable for IDMx6x zone 1, cable length 3 m, straight	265948
	VB-IDMx6x-EXT-3.0m-Z1-spiral Extension cable for IDMx6x zone 1, cable length 3 m, coiled	263908
	VB-IDMx6x-EXT-6m-Z1 Extension cable for IDMx6x zone 1, cable length: 6 m, straight	224108
	VB-IDMx6x-EXT-6.0m-Z1-spiral Extension cable for IDMx6x zone 1, cable length 6 m, coiled	265949
Power supply		Art. No.
	DSP-IDMx6x-DC5V Power supply for non-ex base loading station	224095
Tripod		Art. No.
	IDMx6x-tripod Tripod for IDMx6x, material: ABS (acrylonitrile-butadiene-styrene)	224106

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.