Installation Equipment and Accessories

Stopping plug With hex head



CMP-757-D-M5-4 Art. No. 253034



- Ex d und Ex e metal stopping plugs
- · Large selection of thread types and sizes
- Operating temperature range: -60 C° to +200 °C
- · Worldwide certification, IECEx, ATEX, UL and cCSAus

MY R. STAHL 757DA



The metal Ex-d stopping plugs from the 757 series with external hexagon and head enable temporary or long-term plugging of unused drilled holes. There is a wide selection of different thread sizes and types available. They have worldwide certification according to IECEx, ATEX, UL and cCSAus.

Technical Data

Explosion Protection	
Application range (zones)	1 2 20 21 22
IECEx gas certificate	IECEx CML 18.0177X
IECEx gas explosion protection	Ex db IIC Gb
IECEX firedamp certificate	IECEx CML 18.0177X
IECEx firedamp protection	Ex db I Mb
IECEx firedamp protection 2	Ex eb I Mb
ATEX gas certificate	CML 18ATEX1320X
ATEX gas explosion protection	
ATEX firedamp certificate	CML 18ATEX1320X
ATEX firedamp protection	
ATEX firedamp protection 2	
Notes	The product certification and certificates can be downloaded from the manufacturer's homepage (www.cmp-products.com)
Ambient Conditions	
Ambient temperature	-60 °C +200 °C
Mechanical Data	
Degree of protection (IP)	IP66
Degree of protection note	IP67 and IP68 mounting in accordance with the specifications of the manufacturer, CMP. The specified degrees of protection are only fulfilled if CMP installation accessories are used.
Degree of protection (IP) UL	IP66
Material	Stainless steel
Silicone-free	Yes

Installation Equipment and Accessories


Stopping plug With hex head



CMP-757-D-M5-4 Art. No. 253034

Mechanical Data	
Drive	External hexagon
Width across corners	50.6 mm
Width across flats	46 mm
Outer diameter	50.6 mm
Thread size	M40
Thread length	15 mm
Thread pitch	1,5
Impact strength (IEC 62262)	IK10
Packaging unit	1
Weight	110 g
Weight	0.24 lb

Dimensional Drawings (All Dimensions in mm [inches]) - Subject to Alterations



A = Thread size

B = Length

L = Thread length

D = Outer diameter

b = Dimension b d = Dimension d

d = Dimension d E = Width across corners

SW = Hexagon socket width across flats

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.