

CMP-050TMC Art. No. 254317



- Designed for use in North America
- Version with NPT thread and metric thread
- Operating temperature range: -60 °C ... +110 °C
- Class I Zone 1, 21 und Zone 2, 22
- Class I Zone 1 Ex e and Class I Div. 2 groups ABCD
- Worldwide certification, UL, cCSAus, IECEx and ATEX

MY R. STAHL TMCA



The cable glands have a sequential design and, therefore, do not need to be dismantled for installation. A 360° rotary spring establishes secure earthing. They have worldwide certification according to UL, cCSAus, IECEx and ATEX.

### Technical Data

#### Explosion Protection

Ex version	Ex e & Ex d & Ex nR & Ex ta
Application range (zones)	1 2 20 21 22
IECEX gas certificate	IECEX CML 18.0184X
IECEX gas explosion protection	Ex db IIC Gb
IECEX firedamp certificate	IECEX CML 18.0184X
IECEX firedamp protection	Ex db I Mb
IECEX firedamp protection 2	Ex eb I Mb
IECEX restricted breathing certificate	IECEX CML 18.0184X
IECEX restricted breathing	Ex nR IIC Gc
ATEX gas certificate	CML 18ATEX1337X
ATEX gas explosion protection	Ex II 2 G Ex db IIC Gb
ATEX dust certificate	CML 18ATEX1337X
ATEX dust explosion protection	Ex II 1 D Ex ta IIIC Da
ATEX firedamp certificate	CML 18ATEX1337X
ATEX firedamp protection	Ex I M2 Ex db I Mb
ATEX firedamp protection 2	Ex I M2 Ex eb I Mb
ATEX restricted breathing certificate	CML 18ATEX1337X
ATEX restricted breathing	Ex II 3 G Ex nR IIC Gc
Notes	The product certification and certificates can be downloaded from the manufacturer's homepage ( <a href="http://www.cmp-products.com">www.cmp-products.com</a> )

#### Ambient Conditions

Ambient temperature	-60 °C ... +110 °C
---------------------	--------------------

#### Mechanical Data


Version	050
---------	-----

CMP-050TMC Art. No. 254317

### Mechanical Data

Degree of protection (IP)	IP66
Degree of protection note	Mounting in accordance with the specifications of the manufacturer, CMP
Material	Nickel-plated brass
Silicone-free	Yes
Clamping range	13 – 17 mm
Clamping range	13 ... 17 mm
Width across corners	39.6 mm
Width across flats	36 mm
Thread size	NPT1/2
Thread length	19.8 mm
Thread pitch	14 TPI
Thread standard	NPT
Inner sheath	13 ... 17 mm
Outer sheath	11.1 ... 20 mm
Protrusion length	52.2 mm
Impact strength (IEC 60079)	7 J
Impact strength	20 J
PVC boot	PVC09
Lot size	1
Weight	280 g
Weight	0.62 lb

### Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



- 1 = removable armour stop
- A = Inner sheath
- B = Outer sheath
- C = Thread size
- D = Width across corners
- D = Width across flats
- E = Thread length
- F = Protrusion length

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.