

IS330.1 Mobile Phone Set ROWno camera Art. No. 317433



- Explosion-protected industrial phone with push-to-talk option
- No camera
- SOS key for lone-worker protection
- NFC access control
- Universal powerful replaceable battery for multiple-shift operation
- Android Enterprise Recommended
- Zero touch capable
- Managed via MDM system

MY R. STAHL MPHONEA



Thanks to its freely programmable key, optionally with PTT, the professional mobile phone can be used like a radio device. Its ISM interface for the connection of other accessories such as RSM or PTT headsets make it suitable for MCPTT communication. The Android Enterprise Recommended device is zero touch capable and can be easily managed via an MDM system. The powerful battery and the charging options via desktop or multi-charger complete the highlights of this ultra-robust mobile device with a comfortable feel.

Technical Data

General

Technology	Telephone
Version	Mobile phone

Explosion Protection

Application range (zones)	1 2 21 22
Application range (divisions)	Class I, Division 1 Class II, Division 1 Class III, Division 1
Application range	Zone 1, Zone 21 Zone 2, Zone 22
Scope	EU (CE / ATEX) Global (IECEX) USA (NEC®) Canada (CE Code) Japan (JNIOOSH)
IECEX certification	EPS 19.0036X
ATEX certification	EPS 19 ATEX 1 073 X
NEC certification	70220247
CEC certification	70220247
JPNEEx certification	CSAUK 21JPN007X CSAUK 21JPN008X
IECEX gas explosion protection	Ex ib IIC T4 Gb
IECEX dust explosion protection	Ex ib IIIC T135°C Db IP6X
ATEX gas explosion protection	Ex II 2G Ex ib IIC T4 Gb
ATEX dust explosion protection	Ex II 2D Ex ib IIIC T135°C Db IP6X

IS330.1 Mobile Phone Set ROWno camera Art. No. 317433

Explosion Protection

NEC gas explosion protection	Class I, Div 1, Groups A, B, C, D, T4
NEC dust explosion protection	Class II, Div 1, Groups E, F, G , T135°C Class III, Div 1
CEC gas explosion protection	Class I, Div 1, Groups A, B, C, D, T4
CEC dust explosion protection	Class II, Div 1, Groups E, F, G , T135°C Class III, Div 1
JNIOSH gas explosion protection	Ex ib IIC T4 Gb
JNIOSH dust explosion protection	Ex ib IIIC Db

Electrical Data

Processor type	Qualcomm SDM660 Octa-core
Main memory	4 GB
Data memory	64 GB int. + SD up to 128GB
Operating system	Android 10
Mobile standard	2G, 3G, 4G
Interface medium	WiFi 802.11 a/b/g/n/ac/e/k/r/h
Optional interface 1	Bluetooth 5
SD card type/size	MicroSD/up to 128 GB
Number of SIM cards	Double SIM
SIM card size	Micro

Display

Display size in inches	2.60
Display size in cm	6.60
Display resolution	320 x 432 pixels
Touchscreen material	Gorilla glass corning 3rd gen.
Backlight	LED technology

Ambient Conditions

Ambient temperature	-20 – 60
---------------------	----------

Mechanical Data

Degree of protection (IP)	IP68
MIL-standard	810G (h/l temp.,shock,vibr.)
Width	60 mm
Height	153 mm
Depth	26 mm
Weight	318 g
Weight	0.7 lb

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.