

8150/5-V88-38127-4406-3306 Art. No. 254867



- Mounting flush with the wall with a hygienic design
- Stainless steel enclosure in AISI 316L with a covered sealing system
- A locked switch prevents the connector from being inadvertently pulled out under load
- Versions with single or dual sockets
- Current levels of 16 A and/or 32 A

MY R. STAHL 8150E

The wall-mounted socket distributors for clean rooms from series 8150/5-V88 have been developed for all applications in which particle contamination can affect the quality, purity or service life of a product. For example, in the pharmaceutical industry an excessive particle content restricts the purity of medication, while in the semiconductor industry particles can shorten the service life of components such as chips, LEDs or touchscreens. Other fields include the optical industry (production of lenses and microscopes), the food industry, and the life science and laboratory sectors. With their clear structure and hygienic design, the socket distributors can be installed flush with the wall in the aforementioned areas according to the necessary classification.

Technical Data

Explosion Protection

| | |
|---------------------------------|--|
| Scope of validity | European Union (ATEX) IECEX India (PESO) |
| Application range (zones) | 1 2 21 22 |
| IECEX gas certificate | IECEX PTB 09.0049 |
| IECEX gas explosion protection | Ex db eb IIC T4 Gb |
| IECEX dust certificate | IECEX PTB 09.0049 |
| IECEX dust explosion protection | Ex tb IIIC T130 °C Db |
| ATEX gas certificate | PTB 09 ATEX 1109 |
| ATEX gas explosion protection | ⊕ II 2 G Ex db eb IIC T4 Gb |
| ATEX dust certificate | PTB 09 ATEX 1109 |
| ATEX dust explosion protection | ⊕ II 2 D Ex tb IIIC T130 °C Db |
| Certificates | ATEX (PTB), Canada (FM), IECEX (PTB) |

Electrical Data

| | |
|--------------------------|-----|
| Looping through possible | Yes |
|--------------------------|-----|

Ambient Conditions

| | |
|---------------------|--------------------|
| Ambient temperature | -50 °C ... +40 °C |
| Ambient temperature | -58 °F ... +104 °F |

Mechanical Data

| | |
|---------------------------------------|------|
| Degree of protection (IP) (IEC 60529) | IP66 |
| IP degree of protection (IEC 60079) | IP64 |

8150/5-V88-38127-4406-3306 Art. No. 254867

Mechanical Data

| | |
|--------------------|---|
| Enclosure material | Stainless steel 1.4404, (AISI 316L), brush finished |
| Silicone-free | No |
| Width | 420 mm |
| Width in inches | 16.535 in |
| Height | 161.5 mm |
| Height, inches | 6.358 in |
| Length | 470 mm |
| Length, inches | 18.51 in |
| Seal | Silicone, foamed |
| Enclosure size | 360x360x91 mm |
| Weight | 12.2 kg |
| Weight | 26.9 lb |

Components

| | |
|------------------------------------|---|
| Stopping plugs | 4 x M25 + 4 x M32 |
| Stopping plug material | Polyamide, black |
| Number of sockets 1 | 1 |
| Socket 1 type | 8571/18 |
| Rated operating voltage socket 1 | 380 ... 415 V |
| Socket 1 frequency | 50/60 Hz |
| Rated operating current socket 1 | 32 A |
| Number of poles on socket 1 | 4 |
| Socket 1 colour code | Red |
| Socket 1 coding | 6 |
| Terminal type socket 1 | Phoenix UT 10 Phoenix UT 10-PE |
| Socket 1 connec. cross-section | 6 mm ² 10 mm ² |
| Socket 1 enclosure material | Polyamide, glass fibre reinforced |
| Switching capacity 1 | AC-3: 690 V/25 A AC-3: 500 V/32 A |
| Switching capacity 1 note | according to IEC/EN 60947-3 |
| Number of sockets 2 | 1 |
| Socket 2 type | 8570/18 |
| Rated operating voltage socket 2 | 200 to 250 V AC |
| Socket 2 frequency | 50/60 Hz |
| Rated operational current socket 2 | 16 A |
| Number of poles on socket 2 | 3 |
| Socket 2 colour code | Blue |
| Socket 2 coding | 6 |
| Terminal type socket 2 | Phoenix UT 6 Phoenix UT 6-PE |
| Socket 2 connec. cross-section | 4 mm ² 6 mm ² |
| Socket 2 enclosure material | Polyamide, glass fibre reinforced |
| Switching capacity 2 | AC-3: 690 V/25 A AC-3: 500 V/32 A |

Installation equipment

Wall-mounted socket distributor for clean rooms




8150/5-V88-38127-4406-3306 Art. No. 254867

Components

| | |
|---------------------------|-----------------------------|
| Switching capacity 2 note | According to IEC/EN 60947-3 |
|---------------------------|-----------------------------|

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations




8150/5-V88 with 1x 8571/18, 32 A and 1x 8570/18, 16 A

Accessories

Dust cover for sockets, series 8570

Art. No.




Retrofittable dust protection for 3-pole sockets

253118

Dust cover for sockets, Series 8571

Art. No.



Retrofittable dust protection for 4-pole sockets

255005

Plug

Art. No.



8570/12-306-S-XX-X-XX-XXX 3-pole plug, 200 to 250 V AC, 50 / 60 Hz, 16 A

272898



8571/12-406-S-XX-X-XX-XXX 4-pole plug, 380 to 415 V AC, 50/60 Hz, 32 A

275687

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.