

Control Devices

Moving iron ammeter For transducer

Ammeter

8403C6-5T-5 Art. No. 262737

STAHL



- Ammeters in various versions, for Ex e enclosures
- Quicker comparison of measured values using externally adjustable red pointers on the device
- On models with CT connection (1 A, 5 A), easy and quick measuring range assignment via retractable scale plate

MY R. STAHL 8403B



R. STAHL Series 8403C6 ammeters are installed in Ex e type of protection enclosures. They provide measured values for circuits which can be quickly compared with the desired values via a red pointer affixed on the outside. The devices work with a moving iron movement with accuracy class 2.5.

Technical Data

Explosion Protection

Scope of validity	European Union (ATEX) IECEX
Ex version	Ex e
Application range (zones)	1 2
IECEX gas certificate	IECEX SIQ 17.0003U
IECEX gas explosion protection	Ex eb IIC T6 ... T4 Gb
IECEX firedamp certificate	IECEX SIQ 17.0003U
IECEX firedamp protection	Ex eb I Mb
ATEX gas certificate	SIQ 17 ATEX 192 U
ATEX gas explosion protection	Ex II 2 G Ex eb IIC T6 ... T4 Gb
ATEX firedamp certificate	SIQ 17 ATEX 192 U
ATEX firedamp protection	Ex I M2 Ex eb I Mb
Marking ULus	Class I, Zone 1 AEx eb IIC T6, T5, T4 Gb U Class I, Div. 2, Groups A,B,C,D, T6
Marking cUL	Class I, Zone 1 Ex eb IIC T6, T5, T4 Gb U Class I, Div. 2, Groups A,B,C,D, T6
Certificates	ATEX (SIQ), Brazil (ULB), IECEX (SIQ), Korea (KGS)

Electrical Data

AC UL rated operational voltage	600 V
Rated insulation voltage	690 V
Frequency	50/60 Hz AC, DC
Rated operational current for AC	5 A
UL rated operational current	5 A
Power dissipation	0.67 VA
Movement	0 to 5 A
Overload scale	5x

Control Devices

Moving iron ammeter For transducer

Ammeter

8403C6-5T-5 Art. No. 262737



Electrical Data

Overload capacity	50 x I _N 1 sec
Frequency range	16 – 100 Hz AC, DC

Ambient Conditions

Ambient temperature	-40 °C ... +40 °C (T6) -40 °C ... +55 °C (T5) -40 °C ... +70 °C (T4)
Ambient temperature	-40 °F ... +104 °F (T6) -40 °F ... +131 °F (T5) -40 °F ... +158 °F (T4)
Ambient temperature note	T6: -40 °C ≤ T _{amb} ≤ +40 °C T5: -40 °C ≤ T _{amb} ≤ +55 °C T4: -40 °C ≤ T _{amb} ≤ +70 °C
Use at the height of	2000 m
Degree of contamination	3

Mechanical Data

Version	for current transducer
Degree of protection (IP)	IP54
Degree of protection (IP) terminals	IP20
Enclosure material	Polycarbonate
Silicone-free	No
Pane material	Glass
Terminals	Screw connector (strain-relief clamp)
Max. USA finely stranded/flexible connection terminals	9 AWG
Connection cross-section	6 mm ²
Min. connection cross section, solid	2,5 mm ²
Max. connection cross section, solid	10 mm ²
Min. connection cross-section, finely stranded	2,5 mm ²
Max. connection cross-section, finely stranded	6 mm ²
Stripping length	10 mm
Stripping length inch	0.39 in
Min. tightening torque	1.2 Nm
Min. tightening torque lb	10.62 lb
Max. tightening torque	1.5 Nm
Max. tightening torque lb	13.27 lb
Width	72 mm
Width in inches	2.83 in
Height	71.2 mm
Height, inches	2.8 in
Depth	72 mm
Depth, inches	2.83 in
Accuracy class	2.5
Weight	310 g
Weight	0.68 lb

Control Devices

Moving iron ammeter For transducer

Ammeter

8403C6-5T-5 Art. No. 262737




Mounting / Installation

Mounting	Variant 1: Engage on DIN rail Variant 2: Mounting with screws on mounting plate
Mounting orientation	Vertical
Max. USA solid connection terminals	7 AWG

Components

Scale	without
-------	---------

Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



Spare Parts

Calotte



72 x 72 mm calotte [2.83 x 2.83 inch]; IP66

Art. No.

155942

Push-in scales

		Art. No.
	Overload: 5 times scale: 0 ... 1 A	265718
	Overload: 5 times scale: 0 ... 5 A	265720
	Overload: 5 times scale: 0 ... 10 A	265722













Control Devices

Moving iron ammeter For transducer

Ammeter

8403C6-5T-5 Art. No. 262737



	Overload: 5 times scale: 0 ... 15 A	265724
	Overload: 5 times scale: 0 ... 20 A	265726
	Overload: 5 times scale: 0 ... 25 A	265728
	Overload: 5 times scale: 0 ... 30 A	265730
	Overload: 5 times scale: 0 ... 40 A	265732
	Overload: 5 times scale: 0 ... 50 A	265734
	Overload: 5 times scale: 0 ... 60 A	265736
	Overload: 5 times scale: 0 ... 75 A	265738
	Overload: 5 times scale: 0 ... 80 A	265740
	Overload: 5 times scale: 0 ... 100 A	265742
	Overload: 5 times scale: 0 ... 150 A	265744
	Overload: 5 times scale: 0 ... 200 A	265746

Control Devices

Moving iron ammeter For transducer

Ammeter

8403C6-5T-5 Art. No. 262737



	Overload: 5 times scale: 0 ... 250 A	265748
	Overload: 5 times scale: 0 ... 300 A	265751
	Overload: 5 times scale: 0 ... 400 A	265753
	Overload: 5 times scale: 0 ... 500 A	265755
Push-in scale according to specification		Art. No.
	Mandatory information A ₂ = Measuring range start value B = Measuring range final value C = Overload value D = Unit	265189

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.