

Switch Barox 24TX+ 4SFP RY-GSP22-26/370 Art. No. 274684



- Integrated cyber security and high user-friendliness
- Maintenance of PoE power supply, active monitoring of the camera
- Active integration of the switch into VMS and PSIM systems
- Active monitoring and management of the video network via the DMS

MY R. STAHL

Why Barox?
Barox specifically tailors the features of its products to meet the high demands of video and security networks. This offers planners, installers and users many practical benefits.
This video-optimised switch has been specifically developed for applications with high data loads, such as Video over IP and video streaming. Thanks to PoE, IP cameras can be powered via the data cable.

Technical Data

General	
Version	Network switch
Description	CCTV switch, L2 manageable, ring-capable and DMS
Electrical Data	
Power supply	100 – 240 VAC, 50 – 60 Hz
Power consumption	max. 40 W (without PoE) / 450 W (with PoE)
Ambient Conditions	
Temperature range	0 °C to +40 °C
Mechanical Data	
Type of installation	Rack mounting
Dimensions (WxHxD)	442 mm x 44 mm x 211 mm
Weight	3.4 kg
Weight	7.5 lb

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.