

KVM XD614P-DP-EURO Art. No. 343497



- High-resolution video on up to four monitors
- Range of up to 4 km with a fibre-optic connection
- Emulated USB 2.0, plug-and-play, flexibility in monitor selection
- Digital audio via DisplayPort, analogue audio via line in/out

MY R. STAHL

The KVM XD614P-DP-EURO is a high-resolution KVM extender with four outputs. High-resolution video, USB 2.0 and audio are transmitted via a single CATx or fibre-optic cable. The KVMA extender is designed to provide reliable, real-time access to critical computers – regardless of location – whilst maintaining the familiar desktop user experience.

Technical Data

General	
Version	Network cabinet solution
Description	KVM connection server carbinet to control room
Electrical Data	
Power supply	via external power supply PSU 18W
Video resolution	4096 x 2160 (1 monitor) 2560 x 1600 (2 monitors) 1920 x 1200 (3 monitors) 1920 x 1200 (4 monitors)
Frame rate	60 Hz
Colour depth	8-Bit
Video information	Supports HD60 Quad-Head or 4K60 Single-Head. Transmitter features a local DisplayPort video pass through (Console Connection).
Interfaces	1x USB 2 True Emulation (HID only), full speed 1x USB 2 True Emulation, full speed
Connections	2x DisplayPort 1.2 1x RJ45 (8p8c) 1x SFP+ 1x RS-232
Audio	In / out Analogue / digital
Audio details	2 channels 1 x 3.5 mm jack socket
Status LED	Multi-coloured status LEDs
Ambient Conditions	
Temperature range	0 °C - 40 °C
Storage temperature	-10 °C - 50 °C
Relative humidity	0 % - 80 % (non-condensing)
Altitude	2000 m

KVM XD614P-DP-EURO Art. No. 343497

Mechanical Data	
Enclosure	Robust metal construction
Dimensions (WxHxD)	186 mm x 39 mm x 148 mm
Scope of delivery	Transmitter and receiver unit as rack-mount modules 2x power supply units with country-specific power cables 1x DisplayPort cable 1x USB cable 1x Audio cable 2 m 1x quick start guide
Weight	1.3 kg
Weight	2.87 lb

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.