

EC-940-AFZ-HDI-O4H-R1 Art. No. 266895



- Ethernet copper connection, PoE possible
- Ex e connection box for easy installation
- Modern IP camera with ONVIF protocol (Profile S) and Full HD
- Day / night - functionality
- Certified acc. to ATEX and IECEx

WebCode **EC940AFZA**



The R. STAHL's EC-940-AFZ zoom camera has an Ex e connection box, making installation in hazardous areas especially easy. This camera is equipped with a Ethernet copper connection and designed for a voltage supply of 230 VAC. Alternatively, power can be supplied via PoE (Power over Ethernet Class 3) if no heating operation is desired. It provides clear images even in difficult light - this is ensured by the 32x optical zoom, the WDR image optimisation and the de-fog function, which sharpens contrast in light fog. The camera is integrated into the surveillance system via the ONVIF protocol (Profile S). These robust surveillance camera in an electropolished stainless steel enclosure (316L) is suitable for temperatures ranging from 10 °C and +60 °C (no heating operation) or -40 °C and +65 °C (with heating operation) and certified acc. to ATEX and IECEx for hazardous areas.

Technical Data

Explosion Protection

Application range (zones)	1 2 21 22
IECEx gas certificate	PTB 16.0032X
IECEx gas explosion protection	Ex db eb IIC T4 Gb
IECEx dust certificate	PTB 16.0032X
IECEx dust explosion protection	Ex tb eb IIIC 135 °C Db
ATEX gas certificate	16 ATEX 1019X
ATEX gas explosion protection	Ex II 2 G Ex db eb IIC T4 Gb
ATEX dust certificate	16 ATEX 1019X
ATEX dust explosion protection	Ex II 2 D Ex tb eb IIIC 135 °C Db

Electrical Data

Rated operational voltage AC	230 V
Rated operational voltage DC	
Rated operational current AC	0.15 A
Interfaces	TX
Connection	Ethernet port LAN 10/100 T

Camera Data

Sensor	1/2.8 CMOS
Lens	f = 4.44 (w) to 142.6 mm (t) From F1.6 to F4.4
Viewing angle	62.8° (wide), 2.23° (tele.)

EC-940-AFZ-HDI-O4H-R1 Art. No. 266895

Camera Data

Focus	Automatic focus
Zoom	32x optical
Resolution	Full HD to 320x180 p
Pixel	Approx. 2.38 megapixels
Accuracy of preset positions	0.02 °
Minimum working distance	1500 mm (wide/tele)
Minimum illumination B/W (ICR-ON)	0.03 lx, F1.6, 1/30s, 50 IRE
Minimum illumination color (ICR-OFF)	0.3 lx F1.6, 1/30S, 50 IRE
Number of streams	Multistream 10 profiles
Frame rate (fps)	H.264 max. 60, MJPEG 15 or 30
S/N ratio	50 dB
Back light compensation	Off / BLC
Electronic shutter	2 to 1/12000s
Compression	H.264, MJPEG
De-fog	Off / Auto / Manual
WDR (dynamic range)	120 dB
White balance	ATW, AWC, manual, internal, External, mercury
Wide Dynamik Range	On/Off

Software

Network protocol	ONVIF profile S
Network Configuration	TCP/IPv4-IPv6, UDP/IPv4-IP6, http, NTP, DHCP, QoS, IGMP, Bonjour
Streaming	Unicast / Multicast

Ambient Conditions

Ambient temperature	-40 °C ... +60 °C
---------------------	-------------------

Mechanical Data







Version	Movable viewing angle
Degree of protection (IP)	IP66
Enclosure material	Stainless steel 1.4404
Surface treatment	Electropolished
Cable length	0 m
Integrated wiper	No
Feature	Ex-e compartment
Package weight	0 kg
Weight	16 kg
Weight	35.27 lb

Accessories

Camera multi-cable armoured

Art. No.

EC-940-AFZ-HDI-O4H-R1 Art. No. 266895

	<p>VB-CAM-MULTI-Ethernet-ARM 1 x Ethernet cable 3 x power supplies 2.5 mm² 7 x data cable 0.34 mm² -60 °C ... +80 °C 19.2 ±0.5 mm outer diameter IEC 60332-1 flame-resistant IEC 60754-2 halogen-free DIN 60811-404 oil-resistant NEK 606 mud-resistant Price per metre</p>	<p>252571</p>
<p>Wall mount Art. No.</p>		
	<p>Wall Bracket EC-940-AFZ Suitable for EC-940-AFZ Material: 316L stainless steel, electropolished Weight: ca. 8 kg Load bearing capacity: max. 40 kg WxH: 200 x 160 x 330 mm</p>	<p>257043</p>
<p>Pole adapter module Art. No.</p>		
	<p>Pole adapter module EC-940-AFZ Suitable for EC-940-AFZ Material: 316L stainless steel, electropolished Weight: ca. 4.7 kg Load bearing capacity: max. 40 kg WxH: 214 x 194 mm For pole diameter 88 ... 150 mm May only be used together with wall bracket EC-940-AFZ type 257043</p>	<p>257047</p>
<p>Corner adapter Art. No.</p>		
	<p>Corner adapter EC-940-AFZ Suitable for EC-940-AFZ series Material: 316L SST, electropolished Load bearing capacity: max. 40 kg WxHxD: 355 x 150 x 211 mm Weight: ca. 3.2 kg May only be used together with wall bracket EC-940-AFZ type 257043</p>	<p>257048</p>
<p>Ceiling holder Art. No.</p>		
	<p>Parapet mounting EC-940-AFZ Suitable for EC-940-AFZ Material: 316L stainless steel, electropolished Weight: ca. 4.5 kg Load bearing capacity: max. 40 kg WxHxD: 200 x 450.5 x 330 mm</p>	<p>257049</p>
<p>PoE++ Extender Art. No.</p>		
	<p>PoE++ Extender EC-940-HDI-O6H Cable type: ideally, CAT5e or better Supports Jumbo Frames up to a max. of 9 kB Input voltage: 52 ... 57 V DC Energy consumption: max. 80 W -20 ... +75 °C LxBxH: 126 x 95.3 x 30 mm</p>	<p>256800</p>

Cameras and CCTV Equipment

Zoom camera AFZ camera



EC-940-AFZ-HDI-O4H-R1 Art. No. 266895

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.