

Emergency luminaire With LED GRP



Technical Data

General:

Product Type: L409/4348-5101-162-1110-11-850011

Electrical Data:

Rated operational voltage AC: 110 ... 240 V

Battery version: NiCd battery, gas-tight

Battery operating voltage: 6 V

Battery capacity: 7.0 Ah

Frequency range: 50 – 60 Hz

Lighting Data:

Number of lamps: 1

Lamp wattage: 45 W

Lamp: LED

Light colour: 5000 K – neutral white

Light distribution: 120°x120° with diffusing glass

Luminaire efficacy: 129 lm/W

Luminous flux: 5810 lm

Operating time: 1.5 h emergency lighting operation

Emergency light output: 35% – 1.5 h

Colour rendering: ≥ 80

Colour temperature: 5000 K

Mechanical Data:

Enclosure material: Polyester resin, Glass fibre reinforced

Enclosure colour: Light grey (RAL 7035)

Diffuser: With diffuser

Sealing material: Silicone

Installed terminal strip: PE + N + L1 + L2 + L3 + L'

Max. solid connection terminals: 6 mm²

Max. finely stranded connection terminals: 4 mm²

Type of connection cable: Finely stranded Solid

Size: 4

Impact strength (IEC 62262): IK10

**Components:**

Cable entry material: Polyamide, black

Threaded plate: 2x plastic

Ballast: LED NLE 80W 110-240V/7Ah/1.5h/

Through wiring: With 6 conductors 2.5 mm²

Drilled holes: 3 x M25

Stopping plug material: Polyamide, black

Example Type: L409/4348-5101-162-1110-11-850011 | Art. No. 278304

Manufacturer: R. STAHL Schaltgeräte GmbH | Am Bahnhof 30 | 74638 WALDENBURG | r-stahl.com