

8150/1-0236-0176-091-3311 Art. No. 278811



- Resistant Ex e terminal boxes made of stainless steel
- Degree of protection IP66
- External earth connection M8
- Version as screw-on cover for other alternatives contact factory
- Equipped as required

### MY R. STAHL 8150L



R. STAHL Series 8150 Ex e terminal boxes are made of brushed stainless steel (DIN 1.4301, ANSI 304 or DIN 1.4404, ANSI 316L) and are particularly resistant. The optimised design and the circumferential protection channel on the cover opening and the silicone seal suitable for the most extreme temperature ranges make the enclosure usable worldwide. Various optional accessories are available.

## Technical Data

### Explosion Protection

Scope of validity	European Union (ATEX) IECEX NEC CEC
Application range (Zones)	1 2 21 22
IECEX gas certificate	IECEX PTB 09.0048
IECEX gas explosion protection	Ex eb IIC T6 ... T4 Gb
IECEX dust certificate	IECEX PTB 09.0048
IECEX dust explosion protection	Ex tb IIIC T80 °C ... T135 °C Db
ATEX gas certificate	PTB 09 ATEX 1108
ATEX gas explosion protection	⊕ II 2 G Ex eb IIC T6 ... T4 Gb
ATEX dust certificate	PTB 09 ATEX 1108
ATEX dust explosion protection	⊕ II 2 D Ex tb IIIC T80 °C ... T135 °C Db
Certification NEC	E177642
Certification CEC	E177642
Certificates	ATEX (PTB), Canada (UL), IECEX (PTB), Taiwan (ITRI), USA (UL)

### Electrical Data

Rated operational voltage AC IEC	690 V
AC UL rated operational voltage	600 V
UL rated operational current	65 A
Current carrying capacity IEC	max. 54 A
Current carrying capacity NEC, CEC	Max. 65 A

8150/1-0236-0176-091-3311 Art. No. 278811

### Ambient Conditions

Ambient temperature °C	-50 °C ... +40 °C (T6) (T80 °C) -50 °C ... +55 °C (T5) (T95 °C) -50 °C ... +85 °C (T4) (T135 °C)
Ambient temperature °F	-58°F ... +104°F (T6) (T80 °C) -58°F ... +131°F (T5) (T95 °C) -58°F ... +185°F (T4) (T135 °C)

### Mechanical Data

Degree of protection IP (IEC 60529)	IP66
Degree of protection (IP) UL	IP66
Enclosure material	Stainless steel 1.4404, (AISI 316L), brush finished
Material note	special version on request
External protective conductor connection	M8
Silicone-free	No
Connection cross-section	10 mm <sup>2</sup>
Connection cross-section AWG	AWG 8
Cover thickness	2 mm
Cover thickness inch	0.079 in
Wall thickness	1.5 mm
Wall thickness, inches	0.059 in
Dimensions (WxHxD)	236.5 x 176.5 x 91 mm
Dimensions (WxHxD) inch	9.3 x 7 x 3.6 inch
Width	236.5 mm
Width, inches	9.311 in
Height	176.5 mm
Height, inches	6.945 in
Depth	91 mm
Depth, inches	3.583 in
Weight	8 kg
Weight	17.64 lb

### Mounting / Installation

Tightening torque of cover screw 1	4.5 Nm
Tightening torque of cover screw 1 lbf in	39.83 lbf in

### Components

Flange and plates	Without flange
Entries installation options/side	Without drilled holes
Terminal rail	35 x 189 mm (1x)
Terminal rail	1.38 x 7.44" (1x)
Type of terminals 1	1 x Phoenix UT 2-conductor, 10 mm <sup>2</sup> , grey
Type of grounding terminal 1	1 x Phoenix UT PE 2-conductor, 10 mm <sup>2</sup> , green-yellow

### Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.