

# Zener Barriers

## Single-channel safety barriers



9001/01-199-010-101 Art. No. 158589



- For the intrinsically safe operation of a wide range of devices, such as HART transmitters, solenoid valves, sensors, zero-potential contacts and many more
- Compact, space-saving devices that are easy to install on a DIN rail
- Quick and efficient installation as barriers can be simultaneously snapped onto DIN rail and connected to ground (ISA - RPI12.06)
- Convenient maintenance and repair through back-up fuse feature

MY R. STAHL 9001A



The 9001 series INTRINSPAK single-channel zener barriers enable the intrinsically safe operation of virtually all field devices. The comprehensive portfolio and the combination of zener barriers cover a wide variety of signals. The devices are incredibly robust and require little space. The back-up fuse is a convenient feature as it is standardized for all variants.

### Technical Data

| Explosion Protection            |   |
|---------------------------------|---|
| Application range (zones)       | 2   |
| Ex interface zone               | 0, 1, 2, 20, 21, 22   |
| IECEX gas certificate           | IECEX PTB 09.0001X  |
| IECEX gas explosion protection  | Ex ec [ia Ga] IIC T4 Gc   |
| IECEX dust certificate          | IECEX PTB 09.0001X  |
| IECEX dust explosion protection | [Ex ia Da] IIIC   |
| ATEX gas certificate            | PTB 01 ATEX 2088 X  |
| ATEX gas explosion protection   | II 3 (1) G Ex ec [ia Ga] IIC T4 Gc  |
| ATEX dust certificate           | PTB 01 ATEX 2088 X  |
| ATEX dust explosion protection  | II (1) D [Ex ia Da] IIIC  |
| FMus certificate                | 3011002   |
| Marking FMus                    | NONINCENDIVE FOR, Class I, Div. 2, Groups A,B,C,D; T4;<br>Class I, Zone 2, Group IIC T4<br>IS connections for Class I,II,III, Div. 1, Groups A,B,C,D,E,F,G;<br>Class I, Zone 0, Groups IIC/IIB<br>Hazardous location when inst. per doc. 90 016 11 31 1 |
| Certificate ULus                | E81680V1S3  |
| Marking ULus                    | For use in Hazardous location, Class I, Div. 2, Groups A,B,C,D; T4<br>Providing IS circuits for<br>Class I,II,III, GROUPS A,B,C,D,E,F,G;<br>per doc. 90 016 11 31 3   |
| Inmetro gas certificate         | UL-BR 12.0353   |
| Inmetro dust certificate        | UL-BR 12.0353   |
| Certificates                    | ATEX (PTB), Brazil (ULB), Canada (FM), China (NEPSI), IECEX (PTB), India (PESO), Korea (KGS), USA (FM), USA (UL)  |
| Declaration of conformity       | ATEX (EUK), China (CCC)   |
| Installation                    | in Zone 2, Class I, Div. 2, and Class I, Zone 2 and in safe area  |
| Further information             | see respective certificate and operating instructions   |

9001/01-199-010-101 Art. No. 158589

### Safety Data

|  |   |               |               |               |
|--|---|---------------|---------------|---------------|
| Max. voltage $U_o/V_{oc}$  | 19.9 V  |               |               |               |
| Max. current $I_o/I_{sc}$  | 10 mA   |               |               |               |
| Max. power $P_o$   | 50 mW   |               |               |               |
| Max. permissible external capacitance $C_o/C_a$ for IIC                | 0.223 $\mu$ F   |               |               |               |
| Max. permissible external inductance $L_o/L_a$ for IIC                 | 330 mH  |               |               |               |
| Max. permissible external capacitance $C_o/C_a$ for IIB                | 1.42 $\mu$ F  |               |               |               |
| Max. permissible external inductance $L_o/L_a$ for IIB                 | 1000 mH   |               |               |               |
| Intrinsically safe limiting values Inductance $L_o$ /capacitance $C_o$ | Jointly connectable inductance $L_o$ /capacitance $C_o$ |               |               |               |
| IIC  | $L_o$ [mH]  | 50 mH         | 1 mH          | 0.100 mH      |
|  | $C_o$ [ $\mu$ F]  | 0.160 $\mu$ F | 0.170 $\mu$ F | 0.220 $\mu$ F |
| IIB  | $L_o$ [mH]  | 50 mH         | 1 mH          | 0.100 mH      |
|  | $C_o$ [ $\mu$ F]  | 0.800 $\mu$ F | 0.99 $\mu$ F  | 1.30 $\mu$ F  |

### Electrical Data

|                                      |                  |
|--------------------------------------|------------------|
| Number of channels                   | 1                |
| Type of voltage                      | DC               |
| Maximum resistance $R_{max}$         | 2320 $\Omega$    |
| Min. resistance $R_{min}$            | 2097 $\Omega$    |
| Maximum output current $I_{max}$     | 6 mA             |
| Potential                            | Positive         |
| Transmission frequency channel 1     | $\leq$ 50 kHz    |
| $I_{leak}$ leakage current for $U_n$ | $\leq$ 2 $\mu$ A |

### Auxiliary Power

|                           |            |
|---------------------------|------------|
| Nominal voltage $V_{nom}$ | 16 V       |
| Power supply              | Controlled |

### Output

|                       |                   |
|-----------------------|-------------------|
| Temperature influence | $\leq$ 0,25 %/10K |
|-----------------------|-------------------|

### Ambient Conditions

|                                  |                                       |
|----------------------------------|---------------------------------------|
| Ambient temperature $^{\circ}$ C | -20 $^{\circ}$ C ... 60 $^{\circ}$ C  |
| Ambient temperature $^{\circ}$ F | -4 $^{\circ}$ F ... +140 $^{\circ}$ F |
| Storage temperature $^{\circ}$ C | -20 $^{\circ}$ C ... 75 $^{\circ}$ C  |
| Storage temperature $^{\circ}$ F | -4 $^{\circ}$ F ... +167 $^{\circ}$ F |
| Max. relative humidity           | 95% average, no condensation          |

### Mechanical Data

|                                     |                        |
|-------------------------------------|------------------------|
| Degree of protection (IP)           | IP40                   |
| Degree of protection note           | according to IEC 60529 |
| Degree of protection (IP) terminals | IP20                   |
| Enclosure material                  | Polyamide 6GF          |
| Number of connection terminals      | 4                      |
| Connection cross section min.       | 1.5 mm <sup>2</sup>    |
| Connection cross-section max.       | 1.5 mm <sup>2</sup>    |
| Connection cross-section AWG        | 16 AWG                 |

# Zener Barriers

## Single-channel safety barriers



9001/01-199-010-101 Art. No. 158589



### Mechanical Data

|                          |                          |
|--------------------------|--------------------------|
| Type of connection cable | Finely stranded<br>Solid |
| Width                    | 103 mm                   |
| Width, inches            | 4.09 in                  |
| Length                   | 12 mm                    |
| Length in inches         | 0.48 in                  |
| Mounting depth           | 72 mm                    |
| Mounting depth in inches | 2.76 in                  |
| Weight                   | 110 g                    |
| Weight                   | 0.24 lb                  |


### Mounting / Installation

|                                      |                   |
|--------------------------------------|-------------------|
| Earthing connection cross-section    | 4 mm <sup>2</sup> |
| Earthing conductor cross-section AWG | 12 AWG            |
| Connection type                      | 2 PA              |
| Min. torque, Nm                      | 0.5 N · m         |
| Min. torque, lb/in                   | 4.43 lb/in        |
| Max. torque, Nm                      | 0.6 N · m         |
| Max. torque, lb/in                   | 5.31 lb/in        |


### Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



Mounting on DIN rail NS 35/15



Mounting on DIN rail NS 32 by means of adaptor and mounting attachment, moulded plastic



Mounting on mounting plate by means of adaptor

## Accessories

### Terminal block




|  | Art. No. |
|--|----------|
| Phoenix Contact terminal block UT 4-PE | 113057   |
| Phoenix Contact terminal block UT 6-PE | 113058   |


# Zener Barriers


## Single-channel safety barriers




9001/01-199-010-101 Art. No. 158589

| <b>Adaptor</b>   |  | <b>Art. No.</b> |
|--|--|-----------------|
|  | The adaptor enables a zener barrier to be installed on a clamping base (Art. No. 165283) or mounting plate from a previous series. | 158826          |

| <b>Clamping base, moulded material</b>   |   | <b>Art. No.</b> |
|--|---|-----------------|
|  | Enables mounting of zener barrier on a G-rail. The safety barrier is mounted using the adaptor (Art. No. 158826). | 165283          |

| <b>Fuse holder</b>   |   | <b>Art. No.</b> |
|--|---|-----------------|
|  | Fuse holder is snapped onto the side of the zener barrier and can be equipped with up to 5 back-up fuses (replacement). | 158834          |

## Spare Parts

| <b>Back-up fuse</b>  |   | <b>Art. No.</b> |
|--|---|-----------------|
|  | For all zener barriers Series 9001, 9002 and 9004<br>unit: 5 pcs. | 158964          |

| <b>Label carrier</b>   |                                 | <b>Art. No.</b> |
|--|---------------------------------|-----------------|
|  | Transparent cover for the label | 158977          |

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.