## **HMI Systems - Sales Support Form**

Contact inf	formation:											
Customer:										_	Date:	
Email:					Cor	npany nam Cit					State:	
						-	·					
	ons and applic do you plan to inst		s?									
Zone 1		one 21	Zone 22		Class I, Div.	2	Class II,	Div. 1	Class II, D	)iv. 2		
Which certifica	ates do you need f	or the HMI′s	\$?									
IECEx (Global)	ATEX NE (Europe) (U	EC SA)	CEC (Canada)	INMETRO (Brazil)	KCC (Korea)	Othe	er:					
Application:		nshore	Tankfarm	Chemical ind								
	Pharmaceutical in	ndustry	Machinery	Other:								
Technolog	y and display	size										
	erature range are y			the HMI?		°F to		°F				
-	lls do you need for PLC System you wa			2		pcs.						
KVM System	e technology a n Series 600	ana aispi	ay size yo	ou wish to t	use.							
			LOCAL MONITOR					15"	(1024 x 76	8 pixels)		
1				VGA / DVI	-			21.5"	(1920 x 10	)80 pixels)		
	CAT7 < 150M FIBER OPTIC < 10XM		KVM-0VI-83X	EYBOARD / MOUSE / USB	= ĸ							
15" / 21.5" / 22" / 24" / 24	rwu		AVIE-OVI-OUA					24"	(1920 x 10	180 pixels)		
Thin Client S Industrial PC	System Series 5 C Series 400	00 or										
		NETWOR	K DCS			10"	(800 x 60	00 pixels)	ATOM E38	345 Quad CPU	Win10 En	terprise LTSB
	ETHERNET CAT7 < 100M		Workstations		38	15"	(1024 x 7	768 pixels)	AMD Dual	Core	Thin Clien	t Firmware
	ERER OPTIC < 10KM		DRDC / RDP / VNC			21.5"	(1920 x 1	1080 pixels)	Intel Core	i5	PXE BOO	T for Thin Manager
15" / 19" / 21.5" / 22" / 24"				ZDC zneitstzkoW leateV		24"	<b>(1920 x</b> 1	1080 pixels)				
Operator Int	erface - Raptor	200 Sorio	s - Eagle 3(	10 Sorios (wi	th Runtime)							
	and the second sec			SERIAL				7"	(800 x 480	) pixels)	Movicon (	E
	SERIAL RS-485 / RS-422 ETHERNET CAT5 < 1		-	MPI	PLC			10"		) pixels)	CODESYS WebVisu	
EXICO/ 10-715-	FIBER OPTIC < 28	(2.7.7.)	SPSPlus	IBUS / MPI WIN / Mavican / Engineering /NC Viewer / Remote Access	B							
-			NETWORK	Soft-SPS R				15"		8 pixels)	SPS PLUS RT	
Touchscreen:	Ye	es		No			Ethernet	t connection:	Copper	Dual Copper	Fiber Optic	WIFI
Power supply:	: 11	0 / 230 V AG	C	24 V DC			Highbrig	htness display:	Yes	No		
Mounting a	and keyboard											
HMI Installatio												
Panel mount:			Wall mount: Enclosu	re type:		Pedestal m	ount:					
			Standard enclosure Enclosure material:			Cleanroom enclosure						
			Lindidad	304 SS		316 SS						
Would a Keybo	oard be required? No		Yes									
	NC.	,	Pointing De	vice:								
				Trackball		Joystick		Touchpad				
Accessorie	es and notes											
RFID Reader:		Ethernet	Extender:	100 Mbit / 25	60 m	Barcodesc	anner:	Wired Wireless		1-D 2-D	Emergen	cy stop:
Other Impor	tant Information	n / Add-on:	s concernii	ng the applic	ation:							
	e not possible in a							on.				
Sena your	configuration	to Autor	nationtea	n@r-stanl.	com to req	uest a qu	ole.					

For more product information, visit us at www.rstahl.com.

STAHL